

SAFETY DATA SHEET.

Issuing date 27-Oct-2016 Revision Date 27-Oct-2016 Version 1.01

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product name MS-1011 HEAVY DUTY SILICONE SPRAY

Recommended use of the chemical

and restrictions on use

Product code F00130

Product Type Highly flammable aerosol

Synonyms None

Supplier's details

Recommended Use Silicone lubricant.
Uses advised against No information available

Manufactured For: Mark Supply, Inc. P.O. Box 1451 Venice, FL 34285

Emergency telephone number

Chemical Emergency Phone INFOTRAC: 800-535-5053

Number

Company Emergency Phone 941-485-8199

Number

Page 1/10

2. HAZARDS IDENTIFICATION

Classification

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2B
Reproductive Toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration toxicity	Category 1
Flammable aerosols	Category 1
Gases under pressure	Compressed Gas

GHS Label elements, including precautionary statements

Emergency Overview

DANGER

Hazard Statements

Causes skin irritation

Causes serious eye irritation

Suspected of damaging fertility or the unborn child

May cause respiratory irritation. May cause drowsiness or dizziness.

May cause damage to organs. (Central Nervous System, Peripheral Nervous System, Eyes, Kidney, Liver, Lungs, Respiratory System, Skin, Blood, and Hematopoietic System) through prolonged or repeated exposure.

May be fatal if swallowed and enters airways

Highly flammable aerosol

Contains gas under pressure; may explode if heated



Appearance Clear

Physical state Aerosol

Odor Solvent

Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Wear protective gloves/protective clothing/eye protection/face protection

Wash face, hands and any exposed skin thoroughly after handling

Do not breathe dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces.-No smoking.

Do not spray on an open flame or other ignition source.

Pressurized container: Do not pierce or burn, even after use

Precautionary Statements - Response

If exposed or concerned: Get medical advice/attention.

Specific treatment (see first aid on this label)

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention

IF ON SKIN: Wash with plenty of soap and water.

Take off contaminated clothing and wash it before reuse

If skin irritation occurs: Get medical advice/attention

Page 2/10

F00130 - MS-1011 SILICONE SPRAY

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a POISON CENTER or doctor/physician if you feel unwell

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician Do NOT induce vomiting

Precautionary Statements - Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

None

Other information

· Toxic to aquatic life with long lasting effects

0.000003% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %*
PROPANE/ISOBUTANE/N-BUTANE	68476-86-8	50-60
HEXANE	110-54-3	30-40
PETROLEUM DISTILLATES	64741-65-7	1-10

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

First aid measures for different exposure routes

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep

eye wide open while rinsing. If symptoms persist, call a physician.

Skin contact Wash off immediately with soap and plenty of water while removing all contaminated

clothes and shoes. If skin irritation persists, call a physician.

Inhalation Move to fresh air. If breathing is difficult, give oxygen, Artificial respiration and/or oxygen

may be necessary. If breathing has stopped, contact emergency medical services

immediately.

Ingestion Rinse mouth. Do NOT induce vomiting. Never give anything by mouth to an unconscious

person. Drink plenty of water. Call a physician or Poison Control Center immediately.

Most important symptoms/effects, acute and delayed

Main Symptoms May cause skin and eye irritation. May be irritating to respiratory system. Harmful if

swallowed.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media Decomposition by contact with water may generate vapors which can be ignited by heat or

open flame.

Specific hazards arising from the chemical

Explosion Data

Sensitivity to Mechanical Impact none. Sensitivity to Static Discharge none.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with skin, eyes and clothing. Avoid breathing vapors or mists. Use with

adequate ventilation. Keep can away from heat, flames, and all other sources of ignition. Keep can away from all sources of electricity such as electric motors and batteries. Do not

spray on hot surfaces.

Environmental precautions

Environmental precautions Vapors can accumulate in low areas. Prevent further leakage or spillage if safe to do so. Do

not allow material to contaminate ground water system. Prevent product from entering

drains.

Methods and materials for containment and cleaning up

Methods for Containment Absorb with earth, sand or other non-combustible material and transfer to containers for

later disposal. Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Pick up and transfer to properly labeled containers. Soak up with inert absorbent material.

Clean contaminated surface thoroughly. After cleaning, flush away traces with water. Prevent product from entering drains. Take precautionary measures against static

discharges.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Avoid contact with skin, eyes and clothing. Handle in accordance with good industrial

hygiene and safety practice. Remove and wash contaminated clothing before re-use. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures

against static discharges.

Conditions for safe storage, including any incompatibilities

Technical measures/Storage

conditions

Keep containers tightly closed in a dry and well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition. Keep in properly labeled containers. Keep out

of the reach of children. Store locked up.

Incompatible products Store away from strong acids, alkalis, oxidizing agents.

Aerosol Level 3

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
PROPANE/ISOBUTANE/N-BUTANE 68476-86-8	74-98-6: TWA: 1000 ppm 106-97-8: STEL: 1000 ppm 75-28-5: STEL: 1000 ppm	74-98-6:TWA: 1000 ppm TWA: 1800 mg/m³ (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m³ 106-97-8: (vacated) TWA: 800 ppm (vacated) TWA: 1900 mg/m³	74-98-6:IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m³ 106-97-8:TWA: 800 ppm TWA: 1900 mg/m³ 75-28-5:TWA: 800 ppm TWA: 1900 mg/m³
HEXANE 110-54-3	TWA: 50 ppm Skin - potential significant contribution to overall exposure by the cutaneous route	TWA: 500 ppm TWA: 1800 mg/m³ (vacated) TWA: 50 ppm (vacated) TWA: 180 mg/m³	IDLH: 1100 ppm TWA: 50 ppm TWA: 180 mg/m³

ACGIH: (American Conference of Governmental Industrial Hygienists)

OSHA: (Occupational Safety & Health Administration) NIOSH IDLH: Immediately Dangerous to Life or Health

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

Exposure controls

Engineering Measures Showers

Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/Face Protection Safety glasses with side-shields.

Skin and body protection Chemical resistant apron. Protective gloves.

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

provided in accordance with current local regulations.

Hygiene measures Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and chemical properties

Physical state Aerosol

Appearance Clear Odor Solvent

Color clear Odor Threshold

Property Values Remarks • Methods

pH No information available
Melting/freezing point No information available

Boiling point/boiling range

Flash Point -96.4 °C / -141 °F Based on propellant Evaporation rate No information available

Evaporation rate

Flammability (solid, gas)

Flammability Limits in Air

No information available
No information available

Revision Date 27-Oct-2016

upper flammability limit lower flammability limit

Vapor pressure Vapor density

Specific Gravity .599

Water solubility Practically insoluble

Partition coefficient: n-octanol/water

Autoignition temperature

No information available

Decomposition temperature

Viscosity

No information available

Explosive properties

Other information

VOC Content(%) 94.12

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to Avoid

Extremes of temperature and direct sunlight.

Incompatible Materials

Store away from strong acids, alkalis, oxidizing agents.

Hazardous Decomposition Products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation Vapors may irritate throat and respiratory system. May cause respiratory irritation; or may

cause drowsiness or dizziness. May cause irritation of respiratory tract. Avoid inhaling

vapors or mists.

Eye contact Irritating to eyes. Irritating to eyes .

Skin contact May cause an allergic reaction with skin if in direct contact. Repeated exposure may cause

skin dryness or cracking. May cause skin irritation and causes serious eye irritation. May be fatal if swallowed and enters airways. Suspected causing cancer. Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure. May cause respiratory irritation; or may cause drowsiness or dizziness. Avoid

contact with skin.

Ingestion May be fatal if swallowed and enters airways. Aspiration into the lungs during swallowing

may be harmful.

Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation

F00130 - MS-1011 SILICONE SPRAY

PROPANE/ISOBUTANE/N-BUTAN	ŧ	-	=31mg/L (Rat) 4 hr
68476-86-8			
HEXANE 110-54-3	= 25 g/kg (Rat)	= 3000 mg/kg(Rabbit)	= 48000 ppm (Rat) 4 h
PETROLEUM DISTILLATES 64741-65-7	> 7000 mg/kg (Rat)	> 2000 mg/kg(Rabbit)	> 5.04 mg/L (Rat) 4 h

Information on toxicological effects

Symptoms May cause eye irritation. May be harmful if swallowed and enters airways.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization None known.

Germ Cell Mutagenicity
Not acutely toxic. May be harmful if swallowed.
There are no carcinogenic chemicals in this product.

Reproductive toxicity Product is or contains a chemical which is a known or suspected reproductive hazard.

Specific target organ systemic May cause drowsiness and dizziness. May cause drowsiness and dizziness.

toxicity (single exposure)
Specific target organ systemic
toxicity (repeated exposure)

cicity (repeated exposure)
Target Organ Effects Cent

Causes damage to Target Organs.

Central Nervous System, Peripheral Nervous System, Eyes, Kidney, Liver, Lungs, Respiratory System, Skin, Blood, and Hematopoietic System) through prolonged or repeated exposure, Central Nervous System, Eyes, Kidney, Liver, Peripheral Nervous System, Respiratory System, Skin, Central Vascular System, and Lungs, Central Nervous System, Peripheral Nervous System, Eyes, Kidney, Liver, Lungs, Respiratory System, Skin, Blood, and Hematopoietic System through prolonged or repeated exposure, Central Nervous System, Peripheral Nervous System, Eyes, Kidney, Liver, Lungs, Respiratory System, Skin, Blood and Hematopoietic System, Central Nervous System, Peripheral Nervous System, Eyes, Kidney, Liver, Lungs, Respiratory System, Skin, Blood and

Hematopoietic System.

Aspiration hazard May be toxic if swallowed and enters airways.

Numerical measures of toxicity - Product Information

Unknown Acute Toxicity 0.000003% of the mixture consists of ingredient(s) of unknown toxicity

The following values are calculated based on chapter 3.1 of the GHS document

 ATEmix (oral)
 67113 mg/kg

 ATEmix (dermal)
 8054 mg/kg

 ATEmix (inhalation-vapor)
 128857 mg/l

12. ECOLOGICAL INFORMATION

This product contains a chemical which is listed as a severe marine pollutant according to DOT.

Ecotoxicity

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to microorganisms	Toxicity to daphnia and other aquatic invertebrates
PROPANE/ISOBUTANE/N- BUTANE 68476-86-8		-	-	-
HEXANE 110-54-3	-	2.1 - 2.98 mg/L LC50 Pimephales promelas 96h flow-through		-
PETROLEUM DISTILLATES 64741-65-7	30000 mg/L EC50 Pseudokirchneriella subcapitata 72h	-	¥	2 mg/L LC50 Mysidopsis bahia 48h

Persistence and degradability

Revision Date 27-Oct-2016

F00130 - MS-1011 SILICONE SPRAY

Bioaccumulation

Chemical Name	log Pow	
PROPANE/ISOBUTANE/N-BUTANE 68476-86-8	<=2.8	

Other adverse effects No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment

Waste Disposal Methods This material, as supplied, is a hazardous waste according to federal regulations (40 CFR

261). Dispose of in accordance with federal, state, and local regulations.

Contaminated packaging Do not re-use empty containers.

14. TRANSPORT INFORMATION

DOT Ground CONSUMER COMMODITY ORM-D

LIMITED QUANTITY

Marine Pollutant This product contains a chemical which is listed as a severe marine pollutant according to

DOT.

IATA UN1950, AEROSOLS, FLAMMABLE, 2.1, LTD. QTY.

IMDG UN1950, AEROSOLS, FLAMMABLE, 2.1, LTD, QTY.

Marine pollutant This product contains a chemical which is listed as a marine pollutant according to

IMDG/IMO

15. REGULATORY INFORMATION

International Inventories

Chemical Name	TSCA	DSL/NDSL	EINECS/ELI NCS	ENCS	IECSC	KECL	PICCS	AICS
PROPANE/ISOBUTA NE/N-BUTANE	Х	Х	Х	Not listed	Х	Х	Х	Х
HEXANE	Х	Х	Х	Х	X	Х	Х	Х
PETROLEUM DISTILLATES	Х	Х	Х	Not listed	Х	Х	Х	Х

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

CHINA - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does contain a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %*	SARA 313 - Threshold Values %
HEXANE - 110-54-3	110-54-3	37.2507	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Star Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	Yes
Reactive Hazard	no

Clean Water Act

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

CERCLA

This material, as supplied, does contain substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
HEXANE 110-54-3	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

U.S. State Regulations

California Proposition 65

This product does not contain any known Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
HEXANE	X	X	X
110-54-3			

EPA Pesticide Registration Number Not applicable

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all the information required by the CPR.

16. OTHER INFORMATION				
NFPA	Health Hazard 2	Flammability 4	Instability 0	Physical and chemical
<u>HMIS</u>	Health Hazard 2	Flammability 4	Physical Hazard 1	hazards - Personal protection B

27-Oct-2016 27-Oct-2016

Issuing date Revision Date Revision Note

Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet