



# Safety Data Sheet

acc. to OSHA, Appendix D to § 1910.1200

## Jade Ceramic Coating - Edge

Version number: GHS 5.1  
Replaces version of: 2017-02-06 (GHS 4)

revision: 2017-03-30

### SECTION 1: Identification

#### 1.1 Product identifier

Trade name **Jade Ceramic Coating - Edge**

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses vehicle coating

#### 1.3 Details of the supplier of the safety data sheet

B&B Blending, LLC  
10963 Leroy Drive  
Northglenn  
CO 80233 United States

Telephone: 1.800.875.6320, 1.303.289.6320

Telefax e-mail: info@bbblending.com

Website: bbblending.com

Competent person responsible for the SDS

Robert Blahnik

e-mail (competent person)

bblahnik@bbblending.com

#### 1.4 Emergency telephone number

Emergency information service

**USA 1.800.535.5053, INTL 1.352.323.3500**  
24 hour emergency telephone number.

### SECTION 2: Hazard(s) identification

#### 2.1 Classification of the substance or mixture

**Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)**

Annex	Hazard class and category	Hazard statement code(s)	
B.6	flammable liquid	Cat. 3 (Flam. Liq. 3)	H226
A.1O	acute toxicity (oral)	Cat. 4 (Acute Tox. 4)	H302
A.2	skin corrosion/irritation	Cat. 2 (Skin Irrit. 2)	H315
A.3	serious eye damage/eye irritation	Cat. 2A (Eye Irrit. 2A)	H319
A.7	reproductive toxicity	Cat. 2 (Repr. 2)	H361f

#### Remarks

For full text of H-phrases: see SECTION 16.

#### Hazards not otherwise classified

Very toxic to aquatic life with long lasting effects (GHS category 1: aquatic toxicity - acute and chronic).

#### The most important adverse physicochemical, human health and environmental effects

The product is combustible and can be ignited by potential ignition sources.

#### 2.2 Label elements

**Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)**

**Signal word** warning



# Safety Data Sheet

acc. to OSHA, Appendix D to § 1910.1200

## Jade Ceramic Coating - Edge

Version number: GHS 5.1  
Replaces version of: 2017-02-06 (GHS 4)

revision: 2017-03-30

### Pictograms

GHS02, GHS07,  
GHS08



### Hazard statements

H226	Flammable liquid and vapor.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H361f	Suspected of damaging fertility.

### Precautionary statements

#### **Precautionary statements - prevention**

Obtain special instructions before use.  
Do not handle until all safety precautions have been read and understood.  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Keep container tightly closed.  
Ground/bond container and receiving equipment.  
Use explosion-proof electrical/ventilating/lighting equipment.  
Use only non-sparking tools.  
Take precautionary measures against static discharge.  
Wash thoroughly after handling.  
Do not eat, drink or smoke when using this product.  
Wear protective gloves/eye protection/face protection.

#### **Precautionary statements - response**

IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.  
IF ON SKIN: Wash with plenty of water.  
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
IF exposed or concerned: Get medical advice/attention.  
Specific treatment (see on this label).  
Rinse mouth.  
If skin irritation occurs: Get medical advice/attention.  
If eye irritation persists: Get medical advice/attention.  
Take off contaminated clothing and wash it before reuse.  
In case of fire: Use sand, carbon dioxide or powder extinguisher to extinguish.

#### **Precautionary statements - storage**

Store in a well-ventilated place. Keep cool.  
Store locked up.

#### **Precautionary statements - disposal**

Dispose of contents/container in accordance with local/regional/national/international regulations.

#### **Hazardous ingredients for labelling**

octamethylcyclotetrasiloxane, organic polysilazane compound



# Safety Data Sheet

acc. to OSHA, Appendix D to § 1910.1200

## Jade Ceramic Coating - Edge

Version number: GHS 5.1  
Replaces version of: 2017-02-06 (GHS 4)

revision: 2017-03-30

### 2.3 Other hazards

There is no additional information.

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

not relevant (mixture)

### 3.2 Mixtures

#### Description of the mixture

Name of substance	Identifier	Wt%	Hazard class and category	Hazard statement
octamethylcyclotetrasiloxane	CAS No 556-67-2	50 - < 75	B.6 A.7 Flam. Liq. 3 Repr. 2	H226 H361f
organic polysilazane compound	CAS No 475645-84-2	10 - < 25	B.6 A.10 A.2 A.3 Flam. Liq. 1 Acute Tox. 4 Skin Corr. 1A Eye Dam. 1	H224 H302 H314 H318
decamethylcyclopentasiloxane	CAS No 541-02-6	10 - < 25	B.6 Flam. Liq. 4	H227
aminofunctional silicone fluid	CAS No 69430-37-1	1 - < 5	B.6 Flam. Liq. 2	H225

For full text of abbreviations: see SECTION 16. Exact percentage of ingredients is withheld as a trade secret.

## SECTION 4: First-aid measures

### 4.1

#### General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

#### Following inhalation

In case of respiratory tract irritation, consult a physician. Provide fresh air.

#### Following skin contact

After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water.

#### Following eye contact

Irrigate copiously with clean, fresh water, holding the eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing.

#### Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.



# Safety Data Sheet

acc. to OSHA, Appendix D to § 1910.1200

## Jade Ceramic Coating - Edge

Version number: GHS 5.1  
Replaces version of: 2017-02-06 (GHS 4)

revision: 2017-03-30

### SECTION 5: Fire-fighting measures

#### 5.1 Extinguishing media

##### Suitable extinguishing media

water spray, BC-powder, carbon dioxide (CO<sub>2</sub>)

##### Unsuitable extinguishing media

water jet

#### 5.2 Special hazards arising from the substance or mixture

In case of insufficient ventilation and/or in use, may form flammable/explosive vapor-air mixture. Solvent vapors are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

##### Hazardous combustion products

nitrogen oxides (NO<sub>x</sub>), carbon monoxide (CO), carbon dioxide (CO<sub>2</sub>)

#### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

##### For non-emergency personnel

Remove persons to safety.

##### For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

#### 6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

#### 6.3 Methods and material for containment and cleaning up

##### Advices on how to contain a spill

Covering of drains.

##### Advices on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage (sawdust, kieselgur (diatomite), sand, universal binder).

##### Appropriate containment techniques

Use of adsorbent materials.

##### Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

#### 6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal precautions: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.



# Safety Data Sheet

acc. to OSHA, Appendix D to § 1910.1200

## Jade Ceramic Coating - Edge

Version number: GHS 5.1  
Replaces version of: 2017-02-06 (GHS 4)

revision: 2017-03-30

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

##### Recommendations

##### Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools.

##### Warning

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapors are heavier than air, spread along floors and form explosive mixtures with air. Vapors may form explosive mixtures with air.

##### Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

#### 7.2 Conditions for safe storage, including any incompatibilities

##### Managing of associated risks

##### • Explosive atmospheres

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.

##### • Flammability hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.

##### Incompatible substances or mixtures

Observe compatible storage of chemicals.

##### Consideration of other advice

##### Ventilation requirements

Use local and general ventilation. Ground/bond container and receiving equipment.

##### Packaging compatibilities

Only packagings which are approved (e.g. acc. to DOT) may be used.

#### 7.3 Specific end use(s)

See section 16 for a general overview.



# Safety Data Sheet

acc. to OSHA, Appendix D to § 1910.1200

## Jade Ceramic Coating - Edge

Version number: GHS 5.1  
Replaces version of: 2017-02-06 (GHS 4)

revision: 2017-03-30

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

##### National limit values

##### Occupational exposure limit values (Workplace Exposure Limits)

No information available.

##### Relevant DNELs/DMELs/PNECs and other threshold levels

No data available.

#### 8.2 Exposure controls

##### Appropriate engineering controls

General ventilation.

##### Individual protection measures (personal protective equipment)

##### Eye/face protection

Wear eye/face protection.

##### Skin protection

##### • hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

##### • other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

##### Respiratory protection

In case of inadequate ventilation wear respiratory protection.

##### Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

##### Appearance

Physical state	liquid
Color	different
Odor	penetrating - like solvent

##### Other physical and chemical parameters

pH (value)	not determined
Melting point/freezing point	not determined
Initial boiling point and boiling range	64.6 °C
Flash point	44 – 48 °C at 101.3 kPa 112 – 119 °F at 1 atm (closed cup)
Evaporation rate	not determined
Flammability (solid, gas)	not relevant (fluid)
Explosive limits	not determined
Vapor pressure	132 Pa at 25 °C
Density	0.97 g/ml at 25 °C 8.11 lb/gal at 25 °C



# Safety Data Sheet

acc. to OSHA, Appendix D to § 1910.1200

## Jade Ceramic Coating - Edge

Version number: GHS 5.1  
Replaces version of: 2017-02-06 (GHS 4)

revision: 2017-03-30

Solubility(ies)	not determined
Partition coefficient	
n-octanol/water (log KOW)	this information is not available
Auto-ignition temperature	645.2 K
Viscosity	not determined
Explosive properties	none
Oxidizing properties	none

### SECTION 10: Stability and reactivity

#### 10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s): risk of ignition

• **if heated**

risk of ignition

#### 10.2 Chemical stability

See below "Conditions to avoid".

#### 10.3 Possibility of hazardous reactions

No known hazardous reactions.

#### 10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

**Hints to prevent fire or explosion**

Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

**Physical stresses which might result in a hazardous situation and have to be avoided**

strong shocks

#### 10.5 Incompatible materials

There is no additional information.

#### 10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

### SECTION 11: Toxicological information

#### 11.1 Information on toxicological effects

Test data are not available for the complete mixture.

**Classification procedure**

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

**Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)**

**Acute toxicity**

Harmful if swallowed.



# Safety Data Sheet

acc. to OSHA, Appendix D to § 1910.1200

## Jade Ceramic Coating - Edge

Version number: GHS 5.1  
Replaces version of: 2017-02-06 (GHS 4)

revision: 2017-03-30

### Acute toxicity estimate (ATE)

oral 1,505 mg/kg

### Acute toxicity of components of the mixture

Name of substance	CAS No	Exposure route	ATE
organic polysilazane compound	475645-84-2	oral	301 mg/kg

### Skin corrosion/irritation

Causes skin irritation.

### Serious eye damage/eye irritation

Causes serious eye irritation.

### Respiratory or skin sensitization

Shall not be classified as a respiratory or skin sensitizer.

### Summary of evaluation of the CMR properties

Suspected of damaging fertility.

Shall not be classified as carcinogenic.

Shall not be classified as germ cell mutagenic.

### Carcinogenicity

- National Toxicology Program (United States):
- IARC Monographs

none of the ingredients are listed

none of the ingredients are listed

### Specific target organ toxicity (STOT)

Shall not be classified as a specific target organ toxicant.

### Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

## SECTION 12: Ecological information

### 12.1 Toxicity

Very toxic to aquatic life with long lasting effects.

### Aquatic toxicity (acute)

Shall not be classified as hazardous to the aquatic environment.

### Aquatic toxicity (acute) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
octamethylcyclotetrasiloxane	556-67-2	LC50	>22 µg/l	fish	96 h
octamethylcyclotetrasiloxane	556-67-2	EC50	>1,000 mg/l	aquatic invertebrates	96 h
organic polysilazane compound	475645-84-2	LC50	57.1 mg/l	zebra fish	96 h
decamethylcyclopentasiloxane	541-02-6	LC50	>16 µg/l	fish	96 h
decamethylcyclopentasiloxane	541-02-6	EC50	>2.9 µg/l	aquatic invertebrates	48 h





# Safety Data Sheet

acc. to OSHA, Appendix D to § 1910.1200

## Jade Ceramic Coating - Edge

Version number: GHS 5.1  
Replaces version of: 2017-02-06 (GHS 4)

revision: 2017-03-30

### Aquatic toxicity (chronic)

#### Aquatic toxicity (chronic) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
octamethylcyclotetrasiloxane	556-67-2	LC50	10 µg/l	fish	14 d
octamethylcyclotetrasiloxane	556-67-2	EC50	>500 mg/l	aquatic invertebrates	24 h
decamethylcyclopentasiloxane	541-02-6	LC50	>16 µg/l	fish	14 d
decamethylcyclopentasiloxane	541-02-6	EC50	>15 µg/l	aquatic invertebrates	21 d

### 12.2 Persistence and degradability

#### Degradability of components of the mixture

Name of substance	CAS No	Process	Degradation rate	Time
octamethylcyclotetrasiloxane	556-67-2	carbon dioxide generation	3.7 %	29 d
decamethylcyclopentasiloxane	541-02-6	carbon dioxide generation	0.14 %	28 d

### 12.3 Bioaccumulative potential

Data are not available.

#### Bioaccumulative potential of components of the mixture

Name of substance	CAS No	BCF	Log KOW	BOD5/COD
octamethylcyclotetrasiloxane	556-67-2	12,400	6.488 (25.1 °C)	
decamethylcyclopentasiloxane	541-02-6	7,060	4.76 (22.4 °C)	

### 12.4 Mobility in soil

Data are not available.

### 12.5 Results of PBT and vPvB assessment

Data are not available.

### 12.6 Other adverse effects

Data are not available.



# Safety Data Sheet

acc. to OSHA, Appendix D to § 1910.1200

## Jade Ceramic Coating - Edge

Version number: GHS 5.1  
Replaces version of: 2017-02-06 (GHS 4)

revision: 2017-03-30

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

##### Waste treatment-relevant information

Solvent reclamation/regeneration.

##### Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

##### Waste treatment of containers/packages

Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

##### Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

### SECTION 14: Transport information

14.1	UN number	<b>1993</b>
14.2	UN proper shipping name	<b>Flammable liquid, n.o.s.</b>
	<b>Technical name (hazardous constituents)</b>	octamethylcyclotetrasiloxane, organic polysilazane compound
14.3	Transport hazard class(es)	
	Class	3 (flammable liquids)
14.4	Packing group	III (substance presenting low danger)
14.5	Environmental hazards	none (non-environmentally hazardous acc. to the dangerous goods regulations)
14.6	Special precautions for user	
	There is no additional information.	
14.7	Transport in bulk according to Annex II of MARPOL and the IBC Code	
	The cargo is not intended to be carried in bulk.	

#### Information for each of the UN Model Regulations

##### • Transport of dangerous goods by road or rail (49 CFR US DOT)

Index number	1993
Proper shipping name	Flammable liquid, n.o.s.
Class	3
Packing group	III
Danger label(s)	3



Special provisions (SP)	B1, B52, IB3, T4, TP1, TP29
ERG No	128



# Safety Data Sheet

acc. to OSHA, Appendix D to § 1910.1200

## Jade Ceramic Coating - Edge

Version number: GHS 5.1  
Replaces version of: 2017-02-06 (GHS 4)

revision: 2017-03-30

### • International Maritime Dangerous Goods Code (IMDG)

UN number	1993
Proper shipping name	FLAMMABLE LIQUID, N.O.S.
Class	3
Packing group	III
Danger label(s)	3



Special provisions (SP)	223, 274, 955
Excepted quantities (EQ)	E1
Limited quantities (LQ)	5 L
EmS	F-E, <u>S-E</u>
Stowage category	A

### • International Civil Aviation Organization (ICAO-IATA/DGR)

UN number	1993
Proper shipping name	Flammable liquid, n.o.s.
Class	3
Packing group	III
Danger label(s)	3



Special provisions (SP)	A3, 274
Excepted quantities (EQ)	E1
Limited quantities (LQ)	10 L

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations specific for the product in question

#### National regulations (United States)

##### **Toxic Substance Control Act (TSCA)**

all ingredients are listed or exempt from listing

##### **SARA TITLE III (Superfund Amendment and Reauthorization Act)**

List of Extremely Hazardous Substances (40 CFR 355) (EPCRA Section 302 and 304) none of the ingredients are listed

Specific Toxic Chemical Listings (40 CFR 372) (EPCRA Section 313) none of the ingredients are listed



# Safety Data Sheet

acc. to OSHA, Appendix D to § 1910.1200

## Jade Ceramic Coating - Edge

Version number: GHS 5.1  
Replaces version of: 2017-02-06 (GHS 4)

revision: 2017-03-30

### CERCLA (Comprehensive Environmental Response, Compensation, and Liability Act)

Section 102(A) Hazardous Substances (40 CFR 302.4)

none of the ingredients are listed

### Clean Air Act

none of the ingredients are listed

15.1.2. Drug precursors, Controlled Substances Act (21 U.S.C. § 802)

none of the ingredients are listed

### Industry or sector specific available guidance(s)

#### NPCA-HMIS® III

Hazardous Materials Identification System (American Coatings Association)

Category	Rating	Description
Chronic	*	Chronic (long-term) health effects may result from repeated overexposure.
Health	2	Temporary or minor injury may occur.
Flammability	2	Material that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur.
Physical hazard	1	Material that is normally stable but can become unstable (self-react) at high temperatures and pressures. Material may react non-violently with water or undergo hazardous polymerization in the absence of inhibitors.
Personal protective equipment	-	

#### NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States)

Category	Degree of hazard	Description
Flammability	2	Material that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur.
Health	2	Material that, under emergency conditions, can cause temporary incapacitation or residual injury.
Instability	0	Material that is normally stable, even under fire conditions.
Special hazard		

### Right to Know Hazardous Substance List

none of the ingredients are listed

### Proposition 65 List of chemicals

none of the ingredients are listed

### Relevant European Union (EU) safety, health and environmental provisions

#### Classification according to GHS (1272/2008/EC, CLP)

##### Hazard class

flammable liquid  
acute toxicity (oral)  
skin corrosion/irritation  
serious eye damage/eye irritation  
reproductive toxicity  
hazardous to the aquatic environment - chronic hazard

##### Category Hazard class and category

3 (Flam. Liq. 3)  
4 (Acute Tox. 4)  
2 (Skin Irrit. 2)  
2 (Eye Irrit. 2)  
2 (Repr. 2)  
4 (Aquatic Chronic 4)



# Safety Data Sheet

acc. to OSHA, Appendix D to § 1910.1200

## Jade Ceramic Coating - Edge

Version number: GHS 5.1  
Replaces version of: 2017-02-06 (GHS 4)

revision: 2017-03-30

### SECTION 16: Other information, including date of preparation or last revision

#### 16.2 Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
49 CFR US DOT	49 CFR § 40 U.S. Department of Transportation
Acute Tox.	Acute toxicity
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BOD	Biochemical Oxygen Demand
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
CLP	Regulation (EC) No 1272/2008 on classification, labeling and packaging of substances and mixtures
CMR	Carcinogenic, Mutagenic or toxic for Reproduction
COD	Chemical oxygen demand
DGR	Dangerous Goods Regulations (see IATA/DGR)
DMEL	Derived Minimal Effect Level
DNEL	Derived No-Effect Level
DOT	Department of Transportation (USA)
EmS	Emergency Schedule
ERG No	Emergency Response Guidebook - Number
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
Flam. Liq.	Flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IARC Monographs	IARC Monographs on the Evaluation of Carcinogenic Risks to Humans
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code
log KOW	n-Octanol/water
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")
NFPA® 704	National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States)
NPCA-HMIS® III	National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition
OSHA	Occupational Safety and Health Administration (United States)
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
Repr.	Reproductive toxicity
Skin Corr.	Corrosive to skin



# Safety Data Sheet

acc. to OSHA, Appendix D to § 1910.1200

## Jade Ceramic Coating - Edge

Version number: GHS 5.1  
Replaces version of: 2017-02-06 (GHS 4)

revision: 2017-03-30

Abbr.	Descriptions of used abbreviations
Skin Irrit.	Irritant to skin
vPvB	Very Persistent and very Bioaccumulative

### 16.3 Key literature references and sources for data

- OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200
- 49 CFR § 172.101 Hazardous Materials Table (DOT)

### 16.4 Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards/Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

### 16.5

#### List of relevant phrases (code and full text as stated in chapter 2 and 3)

Code	Text
H224	Extremely flammable liquid and vapor.
H225	Highly flammable liquid and vapor.
H226	Flammable liquid and vapor.
H227	Combustible liquid.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H361f	Suspected of damaging fertility.

### 16.7

#### Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.