



# Safety Data Sheet

acc. to  
29 CFR 1910.1200 App D

## Jade Ceramic Coating - Ice

version number  
GHS 6.0. replaces  
version of 2017-08-28  
GHS 5

revision  
2017-10-30.

### SECTION 1: Identification

- 1.1 Product identifier**  
**Trade name** Jade Ceramic Coating - Ice
- 1.2 Relevant identified uses of the substance or mixture and uses advised against**  
**Relevant identified uses** Vehicle coating
- 1.3 Details of the supplier of the safety data sheet**  
B&B Blending, LLC  
10963 Leroy Drive  
Northglenn  
CO 80233  
United States
- telephone  
1.800.875.6320, 1.303.289.6320  
e-mail: info@bbblending.com  
website  
bbblending.com  
**e-mail (competent person)** Bblahnik@bbblending.com  
(Robert Blahnik)
- 1.4 Emergency telephone number**  
**Emergency information service** USA 1.800.535.5053, INTL 1.352.323.3500  
24 hour emergency number

### SECTION 2: Hazard(s) identification

- 2.1 Classification of the substance or mixture**  
**Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)**

Section	Hazard class	Cat-egory	Hazard class and category	Hazard state-ment
B.6	Flammable liquid	3	Flam. Liq. 3	H226
A.2	Skin corrosion/irritation	2	Skin Irrit. 2	H315
A.3	Serious eye damage/eye irritation	2A	Eye Irrit. 2A	H319
A.7	Reproductive toxicity	2	Repr. 2	H361f
A.10	Aspiration hazard	1	Asp. Tox. 1	H304

For full text of abbreviations: see SECTION 16

#### The most important adverse physicochemical, human health and environmental effects

The product is combustible and can be ignited by potential ignition sources.



# Safety Data Sheet

acc. to  
29 CFR 1910.1200 App D

## Jade Ceramic Coating - Ice

version number  
GHS 6.0. replaces  
version of 2017-08-28  
GHS 5

revision  
2017-10-30.

### 2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Signal word Danger

Pictograms

GHS02, GHS07,  
GHS08



#### Hazard statements

H226 Flammable liquid and vapor.  
H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H361f Suspected of damaging fertility.

#### Precautionary statements

P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233 Keep container tightly closed.  
P240 Ground/bond container and receiving equipment.  
P241 Use explosion-proof electrical/ventilating/lighting equipment.  
P242 Use only non-sparking tools.  
P243 Take precautionary measures against static discharge.  
P264 Wash thoroughly after handling.  
P280 Wear protective gloves/eye protection/face protection.  
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor/physician.  
P302+P352 IF ON SKIN: Wash with plenty of water.  
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308+P313 IF exposed or concerned: Get medical advice/attention.  
P321 Specific treatment (see on this label).  
P331 Do NOT induce vomiting.  
P332+P313 If skin irritation occurs: Get medical advice/attention.  
P337+P313 If eye irritation persists: Get medical advice/attention.  
P362+P364 Take off contaminated clothing and wash it before reuse.  
P370+P378 In case of fire: Use sand, carbon dioxide or powder extinguisher to extinguish.  
P403+P235 Store in a well-ventilated place. Keep cool.  
P405 Store locked up.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

#### Hazardous ingredients for labelling

Octamethylcyclotetrasiloxane  
Distillates (petroleum), hydrotreated light

### 2.3 Other hazards

Hazards not otherwise classified



# Safety Data Sheet

acc. to  
29 CFR 1910.1200 App D

## Jade Ceramic Coating - Ice

version number  
GHS 6.0. replaces  
version of 2017-08-28  
GHS 5

revision  
2017-10-30.

Very toxic to aquatic life with long lasting effects (GHS category 1: aquatic toxicity - acute and/or chronic).

### Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not relevant (mixture).

### 3.2 Mixtures

#### Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS
octamethylcyclotetrasiloxane	CAS No 556-67-2	25 - < 50	Flam. Liq. 3 / H226 Repr. 2 / H361f
decamethylcyclopentasiloxane	CAS No 541-02-6	10 - < 25	Flam. Liq. 4 / H227
polysiloxazane resin	CAS No 475645-84-2	10 - < 25	Flam. Liq. 1 / H224 Acute Tox. 4 / H302 Skin Corr. 1A / H314 Eye Dam. 1 / H318
Distillates (petroleum), hydro-treated light	CAS No 64742-47-8	10 - < 25	Asp. Tox. 1 / H304
aminofunctional silicone fluid	CAS No 69430-37-1	1 - < 5	Flam. Liq. 2 / H225

For full text of abbreviations: see SECTION 16

## SECTION 4: First-aid measures

### 4.1 Description of first-aid measures

#### General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

#### Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

#### Following skin contact

Wash with plenty of soap and water.

#### Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

#### Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.



# Safety Data Sheet

acc. to  
29 CFR 1910.1200 App D

## Jade Ceramic Coating - Ice

version number  
GHS 6.0. replaces  
version of 2017-08-28  
GHS 5

revision  
2017-10-30.

### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

### 4.3 Indication of any immediate medical attention and special treatment needed

none

## SECTION 5: Fire-fighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

Water spray. BC-powder. Carbon dioxide (CO<sub>2</sub>).

#### Unsuitable extinguishing media

Water jet.

### 5.2 Special hazards arising from the substance or mixture

In case of insufficient ventilation and/or in use, may form flammable/explosive vapor-air mixture. Solvent vapors are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

#### Hazardous combustion products

Nitrogen oxides (NO<sub>x</sub>). Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>).

### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

#### For non-emergency personnel

Remove persons to safety.

#### For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

### 6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

### 6.3 Methods and material for containment and cleaning up

#### Advices on how to contain a spill

Covering of drains.

#### Advices on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage. Sawdust. Kieselgur (diatomite). Sand. Universal binder.

#### Appropriate containment techniques

Use of adsorbent materials.



# Safety Data Sheet

acc. to  
29 CFR 1910.1200 App D

## Jade Ceramic Coating - Ice

version number  
GHS 6.0. replaces  
version of 2017-08-28  
GHS 5

revision  
2017-10-30.

### Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

### 6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

#### Recommendations

#### Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools.

#### Specific notes/details

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapors are heavier than air, spread along floors and form explosive mixtures with air. Vapors may form explosive mixtures with air.

#### Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feed-stuffs.

### 7.2 Conditions for safe storage, including any incompatibilities

#### Managing of associated risks

#### Explosive atmospheres

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.

#### Flammability hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.

#### Ventilation requirements

Use local and general ventilation. Ground/bond container and receiving equipment.

#### Packaging compatibilities

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

### 7.3 Specific end use(s)

See section 16 for a general overview.



# Safety Data Sheet

acc. to  
29 CFR 1910.1200 App D

## Jade Ceramic Coating - Ice

version number  
GHS 6.0. replaces  
version of 2017-08-28  
GHS 5

revision  
2017-10-30.

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

These information are not available.

Relevant DNELs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
octamethylcyclotetrasiloxane	556-67-2	DNEL	73 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects
octamethylcyclotetrasiloxane	556-67-2	DNEL	73 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - systemic effects
octamethylcyclotetrasiloxane	556-67-2	DNEL	73 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - local effects
octamethylcyclotetrasiloxane	556-67-2	DNEL	73 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - local effects
decamethylcyclopentasiloxane	541-02-6	DNEL	24.2 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - local effects
decamethylcyclopentasiloxane	541-02-6	DNEL	97.3 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects

Relevant PNECs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
octamethylcyclotetrasiloxane	556-67-2	PNEC	10 mg/l	microorganisms	sewage treatment plant (STP)	short-term (single instance)
octamethylcyclotetrasiloxane	556-67-2	PNEC	0.059 mg/kg	pelagic organisms	sediment	short-term (single instance)
octamethylcyclotetrasiloxane	556-67-2	PNEC	1.7 mg/kg	(top) predators	water	short-term (single instance)
octamethylcyclotetrasiloxane	556-67-2	PNEC	0.44 µg/l	aquatic organisms	freshwater	short-term (single instance)
octamethylcyclotetrasiloxane	556-67-2	PNEC	0.044 µg/l	aquatic organisms	marine water	short-term (single instance)
octamethylcyclotetrasiloxane	556-67-2	PNEC	10 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
octamethylcyclotetrasiloxane	556-67-2	PNEC	3 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
octamethylcyclotetrasiloxane	556-67-2	PNEC	0.3 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
octamethylcyclotetrasiloxane	556-67-2	PNEC	0.59 mg/kg	benthic organisms	sediment	short-term (single instance)
octamethylcyclotetrasiloxane	556-67-2	PNEC	0.16 mg/kg	terrestrial organisms	soil	short-term (single instance)
decamethylcyclopentasiloxane	541-02-6	PNEC	10 mg/l	microorganisms	sewage treatment plant (STP)	short-term (single instance)



# Safety Data Sheet

acc. to  
29 CFR 1910.1200 App D

## Jade Ceramic Coating - Ice

version number  
GHS 6.0. replaces  
version of 2017-08-28  
GHS 5

revision  
2017-10-30.

Relevant PNECs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
decamethylcyclopentasiloxane	541-02-6	PNEC	11 mg/kg	benthic organisms	sediment	short-term (single instance)
decamethylcyclopentasiloxane	541-02-6	PNEC	13 mg/kg	(top) predators	water	short-term (single instance)
decamethylcyclopentasiloxane	541-02-6	PNEC	3.77 mg/kg	terrestrial organisms	soil	short-term (single instance)
decamethylcyclopentasiloxane	541-02-6	PNEC	1.1 mg/kg	pelagic organisms	sediment	short-term (single instance)

### 8.2 Exposure controls

#### Appropriate engineering controls

General ventilation.

#### Individual protection measures (personal protective equipment)

##### Eye/face protection

Wear eye/face protection.

##### Skin protection

##### Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

##### Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

##### Respiratory protection

In case of inadequate ventilation wear respiratory protection.

##### Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### Appearance

Physical state	Liquid
Color	Different



# Safety Data Sheet

acc. to  
29 CFR 1910.1200 App D

## Jade Ceramic Coating - Ice

version number  
GHS 6.0. replaces  
version of 2017-08-28  
GHS 5

revision  
2017-10-30.

<b>Odor</b>	Penetrating - Like solvent
-------------	----------------------------

### Other safety parameters

<b>PH (value)</b>	Not determined
<b>Melting point/freezing point</b>	Not determined
<b>Initial boiling point and boiling range</b>	64.6 °C
<b>Flash point</b>	50 °C at 101.3 kPa 123 °F at 1 atm
<b>Evaporation rate</b>	Not determined
<b>Flammability (solid, gas)</b>	Not relevant Fluid

### Explosive limits

<b>Lower explosion limit (LEL)</b>	0.6 vol%
<b>Upper explosion limit (UEL)</b>	4.9 vol%
<b>Vapor pressure</b>	132 Pa at 25 °C
<b>Density</b>	0.95 g/ml at 25 °C 7.92 lb/gal at 25 °C
<b>Vapor density</b>	This information is not available
<b>Solubility(ies)</b>	Not determined

### Partition coefficient

<b>- n-octanol/water (log KOW)</b>	This information is not available
<b>Auto-ignition temperature</b>	215 °C
<b>Viscosity</b>	Not determined
<b>Explosive properties</b>	None
<b>Oxidizing properties</b>	None

### 9.2 Other information

<b>Temperature class (USA, acc. to NEC 500)</b>	T3 Maximum permissible surface temperature on the equipment: 200 °C
---	--





# Safety Data Sheet

acc. to  
29 CFR 1910.1200 App D

## Jade Ceramic Coating - Ice

version number  
GHS 6.0. replaces  
version of 2017-08-28  
GHS 5

revision  
2017-10-30.

### SECTION 10: Stability and reactivity

#### 10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition.

##### If heated

Risk of ignition.

#### 10.2 Chemical stability

See below "Conditions to avoid".

#### 10.3 Possibility of hazardous reactions

No known hazardous reactions.

#### 10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

##### Hints to prevent fire or explosion

Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

#### 10.5 Incompatible materials

Oxidizers.

#### 10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

### SECTION 11: Toxicological information

#### 11.1 Information on toxicological effects

Test data are not available for the complete mixture.

##### Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

**Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)**

##### Acute toxicity

Shall not be classified as acutely toxic.

Acute toxicity estimate (ATE) of components of the mixture			
Name of substance	CAS No	Exposure route	ATE
polysiloxazane resin	475645-84-2	oral	301 mg/kg

##### Skin corrosion/irritation

Causes skin irritation.

##### Serious eye damage/eye irritation

Causes serious eye irritation.



# Safety Data Sheet

acc. to  
29 CFR 1910.1200 App D

## Jade Ceramic Coating - Ice

version number  
GHS 6.0. replaces  
version of 2017-08-28  
GHS 5

revision  
2017-10-30.

### Respiratory or skin sensitization

Shall not be classified as a respiratory or skin sensitizer.

### Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

### Carcinogenicity

Shall not be classified as carcinogenic.

### Reproductive toxicity

Suspected of damaging fertility.

### Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

### Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

### Aspiration hazard

May be fatal if swallowed and enters airways.

## SECTION 12: Ecological information

### 12.1 Toxicity

Very toxic to aquatic life with long lasting effects.

Aquatic toxicity (acute) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
octamethylcyclotetrasiloxane	556-67-2	LC50	>22 µg/l	fish	96 h
octamethylcyclotetrasiloxane	556-67-2	EC50	>1,000 mg/l	aquatic invertebrates	96 h
decamethylcyclopentasiloxane	541-02-6	LC50	>16 µg/l	fish	96 h
decamethylcyclopentasiloxane	541-02-6	EC50	>2.9 µg/l	aquatic invertebrates	48 h
polysiloxazane resin	475645-84-2	LC50	57.1 mg/l	zebra fish	96 h
Distillates (petroleum), hydrotreated light	64742-47-8	LL50	5 mg/l	fish	96 h
Distillates (petroleum), hydrotreated light	64742-47-8	EL50	1.4 mg/l	aquatic invertebrates	48 h

Aquatic toxicity (chronic) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
octamethylcyclotetrasiloxane	556-67-2	LC50	10 µg/l	fish	14 d
octamethylcyclotetrasiloxane	556-67-2	EC50	>500 mg/l	aquatic invertebrates	24 h
decamethylcyclopentasiloxane	541-02-6	LC50	>16 µg/l	fish	14 d



# Safety Data Sheet

acc. to  
29 CFR 1910.1200 App D

## Jade Ceramic Coating - Ice

version number  
GHS 6.0. replaces  
version of 2017-08-28  
GHS 5

revision  
2017-10-30.

Aquatic toxicity (chronic) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
decamethylcyclopentasiloxane	541-02-6	EC50	>15 µg/l	aquatic invertebrates	21 d
Distillates (petroleum), hydrotreated light	64742-47-8	LL50	17 mg/l	fish	24 h
Distillates (petroleum), hydrotreated light	64742-47-8	EL50	4.6 mg/l	aquatic invertebrates	24 h

### 12.2 Persistence and degradability

Data are not available.

### 12.3 Bioaccumulative potential

Data are not available.

### 12.4 Mobility in soil

Data are not available.

### 12.5 Results of PBT and vPvB assessment

Data are not available.

### 12.6 Other adverse effects

#### Endocrine disrupting potential

The mixture contains substance(s) with an endocrine disrupting potential.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### Waste treatment-relevant information

Solvent reclamation/regeneration.

#### Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

#### Waste treatment of containers/packages

Only packaging which are approved (e.g. acc. to DOT) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

#### Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.



# Safety Data Sheet



acc. to  
29 CFR 1910.1200 App D

## Jade Ceramic Coating - Ice

version number  
GHS 6.0. replaces  
version of 2017-08-28  
GHS 5

revision  
2017-10-30.

### SECTION 14: Transport information

<b>14.1 UN number</b>	1993 Not required
<b>14.2 UN proper shipping name</b> <b>Technical name Hazardous ingredients</b>	Flammable liquid, n.o.s. Octamethylcyclotetrasiloxane Polysiloxazane resin
<b>14.3 Transport hazard class(es)</b> <b>Class</b>	3 Flammable liquids
<b>14.4 Packing group</b>	III Substance presenting low danger
<b>14.5 Environmental hazards</b>	Non-environmentally hazardous acc. to the dangerous goods regulations
<b>14.6 Special precautions for user</b>	There is no additional information.
<b>14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code</b>	The cargo is not intended to be carried in bulk.
<b>14.8 Information for each of the UN Model Regulations</b>	
<b>Transport of dangerous goods by road or rail (49 CFR US DOT)</b>	
<b>Index number</b>	1993
<b>Proper shipping name</b>	Flammable liquid, n.o.s.
<b>Particulars in the shipper's declaration</b>	UN1993, Flammable liquid, n.o.s., (contains: octamethylcyclotetrasiloxane, polysiloxazane resin), 3, III
<b>Class</b>	3
<b>Packing group</b>	III
<b>Danger label(s)</b>	3
	
<b>Special provisions (SP)</b>	B1, B52, IB3, T4, TP1, TP29
<b>ERG No</b>	128
<b>International Maritime Dangerous Goods Code (IMDG)</b>	
<b>UN number</b>	1993
<b>Proper shipping name</b>	FLAMMABLE LIQUID, N.O.S.
<b>Class</b>	3
<b>Marine pollutant</b>	-
<b>Packing group</b>	III
<b>Danger label(s)</b>	3
	
<b>Special provisions (SP)</b>	223, 274, 955
<b>Excepted quantities (EQ)</b>	E1
<b>Limited quantities (LQ)</b>	5 L
<b>EmS</b>	F-E, <u>S-E</u>
<b>Stowage category</b>	A



# Safety Data Sheet

acc. to  
29 CFR 1910.1200 App D

## Jade Ceramic Coating - Ice

version number  
GHS 6.0. replaces  
version of 2017-08-28  
GHS 5

revision  
2017-10-30.

### International Civil Aviation Organization (ICAO-IATA/DGR)

<b>UN number</b>	1993
<b>Proper shipping name</b>	Flammable liquid, n.o.s.
<b>Class</b>	3
<b>Packing group</b>	III
<b>Danger label(s)</b>	3



<b>Special provisions (SP)</b>	A3
<b>Excepted quantities (EQ)</b>	E1
<b>Limited quantities (LQ)</b>	10 L

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations specific for the product in question

##### National regulations (United States)

##### SARA TITLE III (Superfund Amendment and Reauthorization Act)

##### List of Extremely Hazardous Substances (40 CFR 355) (EPCRA Section 302 and 304)

none of the ingredients are listed

##### Specific Toxic Chemical Listings (40 CFR 372) (EPCRA Section 313)

none of the ingredients are listed

##### CERCLA (Comprehensive Environmental Response, Compensation, and Liability Act)

##### Section 102(A) Hazardous Substances (40 CFR 302.4)

none of the ingredients are listed

##### Clean Air Act

none of the ingredients are listed

##### New Jersey Worker and Community Right to Know Act N.J.S.A. 34:5A-1 et. seq.

none of the ingredients are listed

##### California Environmental Protection Agency (Cal/EPA): Proposition 65 Chemicals known to the State to cause cancer or reproductive toxicity

none of the ingredients are listed

##### Industry or sector specific available guidance(s)

##### NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

Category	Rating	Description
Chronic	*	chronic (long-term) health effects may result from repeated overexposure
Health	2	temporary or minor injury may occur
Flammability	2	material that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur
Physical hazard	1	material that is normally stable but can become unstable (self-react) at high temperatures and pressures. Material may react non-violently with water or undergo hazardous polymerization in the absence of inhibitors
Personal protection	-	



# Safety Data Sheet

acc. to  
29 CFR 1910.1200 App D

## Jade Ceramic Coating - Ice

version number  
GHS 6.0. replaces  
version of 2017-08-28  
GHS 5

revision  
2017-10-30.

### NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	2	material that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur
Health	2	material that, under emergency conditions, can cause temporary incapacitation or residual injury
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

### 15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

### SECTION 16: Other information, including date of preparation or last revision

#### Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
2.3		Hazards not otherwise classified: change in the listing (table)	yes

#### Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
49 CFR US DOT	49 CFR § 40 U.S. Department of Transportation
Acute Tox.	Acute toxicity
Asp. Tox.	Aspiration hazard
ATE	Acute Toxicity Estimate
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
DOT	Department of Transportation (USA)
EmS	Emergency Schedule
ERG No	Emergency Response Guidebook - Number
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
Flam. Liq.	Flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)



# Safety Data Sheet

acc. to  
29 CFR 1910.1200 App D

## Jade Ceramic Coating - Ice

version number  
GHS 6.0. replaces  
version of 2017-08-28  
GHS 5

revision  
2017-10-30.

Abbr.	Descriptions of used abbreviations
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")
NPCA-HMIS® III	National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition
OSHA	Occupational Safety and Health Administration (United States)
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
Repr.	Reproductive toxicity
RTECS	Registry of Toxic Effects of Chemical Substances (database of NIOSH with toxicological information)
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
vPvB	Very Persistent and very Bioaccumulative

### Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

### Classification procedure

Physical and chemical properties. The classification is based on tested mixture.

Health hazards. Environmental hazards. The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

### List of relevant phrases (code and full text as stated in chapter 2 and 3)

Code	Text
H224	Extremely flammable liquid and vapor.
H225	Highly flammable liquid and vapor.
H226	Flammable liquid and vapor.
H227	Combustible liquid.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H361f	Suspected of damaging fertility.



# Safety Data Sheet

acc. to  
29 CFR 1910.1200 App D

## Jade Ceramic Coating - Ice

version number  
GHS 6.0. replaces  
version of 2017-08-28  
GHS 5

revision  
2017-10-30.

---

### Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.