

acc. to OSHA, Appendix D to § 1910.1200

### Jade Ceramic Sealant - Marine

Version number: GHS 2.0 Replaces version of: 2016-05-27 (GHS 1)

#### **SECTION 1: Identification**

### 1.1 Product identifier

Trade name

- 1.2 Relevant identified uses of the substance or mixture and uses advised against
  - Relevant identified uses

vehicle coating

Jade Ceramic Sealant - Marine

1.3 Details of the supplier of the safety data sheet B&B Blending, LLC 10963 Leroy Drive Northglenn CO 80233 United States

> Telephone: 1.800.875.6320, 1.303.289.6320 Telefax e-mail: info@bbblending.com Website: bbblending.com Competent person responsible for the SDS

e-mail (competent person)

**1.4 Emergency telephone number** Emergency information service Robert Blahnik bblahnik@bbblending.com

**USA 1.800.535.5053, INTL 1.352.323.3500** 24 hour emergency telephone number.

### SECTION 2: Hazard(s) identification

#### 2.1 Classification of the substance or mixture

#### Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Annex	<ul> <li>Hazard class and category</li> </ul>	- Hazard	statement code(s)	
B.6	flammable liquid	Cat. 3 (F	Flam. Liq. 3)	H226
A.10	acute toxicity (oral)	Cat. 4 (A	Acute Tox. 4)	H302
A.7	reproductive toxicity	Cat. 2 (F	Repr. 2)	H361f

Remarks

For full text of H-phrases: see SECTION 16.

#### Hazards not otherwise classified

Very toxic to aquatic life with long lasting effects (GHS category 1: aquatic toxicity - acute and chronic).

The most important adverse physicochemical, human health and environmental effects The product is combustible and can be ignited by potential ignition sources.

#### 2.2 Label elements


Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200) <u>Signal word</u> warning Pictograms



acc. to OSHA, Appendix D to § 1910.1200

### Jade Ceramic Sealant - Marine

Version number: GHS 2.0 Replaces version of: 2016-05-27 (GHS 1)





#### Hazard statements

H226 H302 H361f Flammable liquid and vapor. Harmful if swallowed. Suspected of damaging fertility.

#### Precautionary statements

#### Precautionary statements - prevention

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Wear protective gloves/eye protection/face protection.

#### Precautionary statements - response

IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF exposed or concerned: Get medical advice/attention.

Rinse mouth.

In case of fire: Use sand, carbon dioxide or powder extinguisher to extinguish.

#### Precautionary statements - storage

Store in a well-ventilated place. Keep cool. Store locked up.

#### Precautionary statements - disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

#### Hazardous ingredients for labelling

octamethylcyclotetrasiloxane, organic polysilazane compound

#### 2.3 Other hazards

There is no additional information.





acc. to OSHA, Appendix D to § 1910.1200

### Jade Ceramic Sealant - Marine

Version number: GHS 2.0 Replaces version of: 2016-05-27 (GHS 1) revision: 2016-10-26

#### SECTION 3: Composition/information on ingredients

#### 3.1 Substances

not relevant (mixture)

#### 3.2 Mixtures

#### Description of the mixture

Name of substance	Identifier	Wt%	Hazard o	class and category	Hazard state- ment
organic polysilazane compound	CAS No 475645-84-2	50 - < 75	B.6 A.1O A.2 A.3	Flam. Liq. 1 Acute Tox. 4 Skin Corr. 1A Eye Dam. 1	H224 H302 H314 H318
octamethylcyclotetrasiloxane	CAS No 556-67-2	25 - < 50	B.6 A.7	Flam. Liq. 3 Repr. 2	H226 H361f
decamethylcyclopentasiloxane	CAS No 541-02-6	5 - < 10	B.6	Flam. Liq. 4	H227
aminofunctional silicone fluid	CAS No 69430-37-1	5 - < 10	B.6	Flam. Liq. 2	H225

For full text of abbreviations: see SECTION 16. Exact percentage of ingredients is withheld as a trade secret.

#### **SECTION 4: First-aid measures**

#### 4.1

#### **General notes**

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

#### Following inhalation

Provide fresh air.

#### Following skin contact

After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water.

#### Following eye contact

Irrigate copiously with clean, fresh water, holding the eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing.

#### **Following ingestion**

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.



acc. to OSHA, Appendix D to § 1910.1200

### Jade Ceramic Sealant - Marine

Version number: GHS 2.0 Replaces version of: 2016-05-27 (GHS 1)

#### SECTION 5: Fire-fighting measures

#### 5.1 Extinguishing media

Suitable extinguishing media

water spray, BC-powder, carbon dioxide (CO2)

Unsuitable extinguishing media water jet

#### 5.2 Special hazards arising from the substance or mixture

In case of insufficient ventilation and/or in use, may form flammable/explosive vapor-air mixture. Solvent vapors are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

#### Hazardous combustion products

nitrogen oxides (NOx), carbon monoxide (CO), carbon dioxide (CO2)

#### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

#### **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

#### For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

#### **6.2 Environmental precautions** Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

#### 6.3 Methods and material for containment and cleaning up

#### Advices on how to contain a spill

Covering of drains.

#### Advices on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage (sawdust, kieselgur (diatomite), sand, universal binder).

#### Appropriate containment techniques

Use of adsorbent materials.

#### Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

#### 6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal precautions: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.





acc. to OSHA, Appendix D to § 1910.1200

### Jade Ceramic Sealant - Marine

revision: 2016-10-26

Version number: GHS 2.0 Replaces version of: 2016-05-27 (GHS 1)

#### **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

#### Recommendations

#### Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools.

#### Warning

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapors are heavier than air, spread along floors and form explosive mixtures with air.

#### Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

#### 7.2 Conditions for safe storage, including any incompatibilities

#### Managing of associated risks

#### • Explosive atmospheres

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.

#### • Flammability hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.

#### Incompatible substances or mixtures

Observe compatible storage of chemicals.

#### Consideration of other advice

#### Ventilation requirements

Use local and general ventilation. Ground/bond container and receiving equipment.

#### Packaging compatibilities

Only packagings which are approved (e.g. acc. to DOT) may be used.

#### 7.3 Specific end use(s)

See section 16 for a general overview.



acc. to OSHA, Appendix D to § 1910.1200



### Jade Ceramic Sealant - Marine

Version number: GHS 2.0 Replaces version of: 2016-05-27 (GHS 1)

#### **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

#### National limit values

Occupational exposure limit values (Workplace Exposure Limits)

No information available.

#### **Relevant DNELs/DMELs/PNECs and other threshold levels** No data available.

-

#### 8.2 Exposure controls

Appropriate engineering controls

General ventilation.

#### Individual protection measures (personal protective equipment)

#### Eye/face protection

Wear eye/face protection.

#### Skin protection

#### hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leaktightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

#### other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

#### **Respiratory protection**

In case of inadequate ventilation wear respiratory protection.

#### **Environmental exposure controls**

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

#### **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

Appearance	
Physical state	liquid
Color	different
Odor	penetrating - like solvent
Other physical and chemical parameters	
pH (value)	not determined
Melting point/freezing point	not determined
Initial boiling point and boiling range	64.6 °C
Flash point	42 - 45 °C at 101.3 kPa 108 - 113 °F at 1 atm (closed cup)
Evaporation rate	not determined
Flammability (solid, gas)	not relevant (fluid)
Explosive limits	not determined
Vapor pressure	132 Pa at 25 °C
Density	0.99 $^{g/}$ <sub>ml</sub> at 25 $^{\circ}$ C 8.31 $^{lb}/$ <sub>gal</sub> at 25 $^{\circ}$ C



acc. to OSHA, Appendix D to § 1910.1200

### Jade Ceramic Sealant - Marine

Version number: GHS 2.0 Replaces version of: 2016-05-27 (GHS 1) revision: 2016-10-26

Solubility(ies)not determinedPartition coefficientnot determinedn-octanol/water (log KOW)this information is not availableAuto-ignition temperature645.2 KViscositynot determinedExplosive propertiesnoneOxidizing propertiesnone

#### **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s): risk of ignition

#### if heated

risk of ignition

#### 10.2 Chemical stability

See below "Conditions to avoid".

### 10.3 Possibility of hazardous reactions

No known hazardous reactions.

#### 10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

#### Hints to prevent fire or explosion

Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

## Physical stresses which might result in a hazardous situation and have to be avoided strong shocks

#### 10.5 Incompatible materials

There is no additional information.

#### 10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

#### **SECTION 11: Toxicological information**

#### 11.1 Information on toxicological effects

Test data are not available for the complete mixture.

#### **Classification procedure**

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).



acc. to OSHA, Appendix D to § 1910.1200

### **Jade Ceramic Sealant - Marine**

Version number: GHS 2.0 Replaces version of: 2016-05-27 (GHS 1)

#### Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

#### Acute toxicity

oral

Harmful if swallowed.

#### Acute toxicity estimate (ATE)

602<sup>mg</sup>/kg

#### Acute toxicity of components of the mixture

Name of substance	CAS No	Exposure route	ATE
organic polysilazane compound	475645-84-2	oral	301 <sup>mg</sup> / <sub>kg</sub>

#### Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

#### Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

#### **Respiratory or skin sensitization**

Shall not be classified as a respiratory or skin sensitizer.

#### Summary of evaluation of the CMR properties

Suspected of damaging fertility.

Shall not be classified as carcinogenic.

Shall not be classified as germ cell mutagenic.

#### Carcinogenicity

• National Toxicology Program (United States):

IARC Monographs

Specific target organ toxicity (STOT)

Shall not be classified as a specific target organ toxicant.

#### Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

#### **SECTION 12: Ecological information**

#### 12.1 Toxicity

Very toxic to aquatic life with long lasting effects.

#### Aquatic toxicity (acute)

Shall not be classified as hazardous to the aquatic environment.

#### Aquatic toxicity (acute) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
organic polysilazane com- pound	475645-84-2	LC50	57.1 <sup>mg</sup> / <sub>l</sub>	zebra fish	96 h
octamethylcyclotetrasilox- ane	556-67-2	LC50	>22 <sup>µg</sup> / <sub>I</sub>	fish	96 h
octamethylcyclotetrasilox- ane	556-67-2	EC50	>1,000 <sup>mg</sup> / <sub>l</sub>	aquatic invertebrates	96 h
decamethylcyclopentasilox- ane	541-02-6	LC50	>16 <sup>µg</sup> / <sub>l</sub>	fish	96 h

revision: 2016-10-26

none of the ingredients are listed

none of the ingredients are listed



acc. to OSHA, Appendix D to § 1910.1200

### Jade Ceramic Sealant - Marine

revision: 2016-10-26

Version number: GHS 2.0 Replaces version of: 2016-05-27 (GHS 1)

Na	me of substance	CAS No	Endpoint	Value	Species	Exposure time
deca	methylcyclopentasilox- ane	541-02-6	EC50	>2.9 <sup>µg</sup> / <sub>l</sub>	aquatic invertebrates	48 h

#### Aquatic toxicity (chronic)

#### Aquatic toxicity (chronic) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
octamethylcyclotetrasilox- ane	556-67-2	LC50	10 <sup>µg</sup> / <sub>l</sub>	fish	14 d
octamethylcyclotetrasilox- ane	556-67-2	EC50	>500 <sup>mg</sup> / <sub>l</sub>	aquatic invertebrates	24 h
decamethylcyclopentasilox- ane	541-02-6	LC50	>16 <sup>µg</sup> / <sub>l</sub>	fish	14 d
decamethylcyclopentasilox- ane	541-02-6	EC50	>15 <sup>µg</sup> / <sub>l</sub>	aquatic invertebrates	21 d

## 12.2 Persistence and degradability

## Degradability of components of the mixture

Name of substance	CAS No	Process	Degradation rate	Time
octamethylcyclotetrasilox- ane	556-67-2	carbon dioxide generation	3.7 %	29 d
decamethylcyclopentas- iloxane	541-02-6	carbon dioxide generation	0.14 %	28 d

#### 12.3 Bioaccumulative potential

Data are not available.

#### Bioaccumulative potential of components of the mixture

Name of substance	CAS No	BCF	Log KOW	BOD5/COD
octamethylcyclotetrasilox- ane	556-67-2	12,400	4.45	
decamethylcyclopentas- iloxane	541-02-6	7,060	4.76 (22.4 °C)	

#### 12.4 Mobility in soil

Data are not available.

#### 12.5 Results of PBT and vPvB assessment

Data are not available.



acc. to OSHA, Appendix D to § 1910.1200

### Jade Ceramic Sealant - Marine

Version number: GHS 2.0 Replaces version of: 2016-05-27 (GHS 1)

#### 12.6 Other adverse effects

Data are not available.

#### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Waste treatment-relevant information

Solvent reclamation/regeneration.

#### Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

#### Waste treatment of containers/packages

Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

#### Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SEC	TION 14: Transport information			
14.1	UN number	1993		
14.2	UN proper shipping name	Flammable liquid, n.o.s.		
	Technical name (hazardous constituents)	organic polysilazane compound, organic polysilazane compound		
14.3	Transport hazard class(es)			
	Class	3 (flammable liquids)		
14.4	Packing group	III (substance presenting low danger)		
14.5	Environmental hazards	NONE (non-environmentally hazardous acc. to the dangerous goods regulations)		
14.6	Special precautions for user There is no additional information.			
14.7	Transport in bulk according to Annex II of MARPOL and the IBC Code The cargo is not intended to be carried in bulk.			
	Information for each of the UN Model Regulations			
	Transport of dangerous goods by road or rail (49 CF)	-		
	Index number	1993		
	Proper shipping name	Flammable liquid, n.o.s.		
	Class	3		
	Packing group	III		
	Danger label(s)	3		
	3			
	Special provisions (SP)	B1, B52, IB3, T4, TP1, TP29		



acc. to OSHA, Appendix D to § 1910.1200

## Jade Ceramic Sealant - Marine

ERG No	128
International Maritime Dangerous Goo	ods Code (IMDG)
UN number	1993
Proper shipping name	FLAMMABLE LIQUID, N.O.S.
Class	3
Packing group	III
Danger label(s)	3
3 Special provisions (SP)	223, 274, 955
Excepted quantities (EQ)	E1
Limited quantities (LQ)	5 L
EmS	F-E, S-E
Stowage category	A
International Civil Aviation Organization	
UN number	1993
Proper shipping name	Flammable liquid, n.o.s.
Class	3
Packing group	III
Danger label(s)	3
Special provisions (SP)	A3, 274
Excepted quantities (EQ)	E1
Limited quantities (LQ)	10 L

### SECTION 15: Regulatory information

## 15.1 Safety, health and environmental regulations specific for the product in question National regulations (United States)

Toxic Substance Control Act (TSCA)	all ingredients are listed or exempt from listing
SARA TITLE III (Superfund Amendment and Reauthorization Act)	
List of Extremely Hazardous Substances (40 CFR 355) (EPCRA Section 302 and 304)	none of the ingredients are listed
Specific Toxic Chemical Listings (40 CFR 372) (EPCRA Section 313)	none of the ingredients are listed



acc. to OSHA, Appendix D to § 1910.1200

### Jade Ceramic Sealant - Marine

Version number: GHS 2.0 Replaces version of: 2016-05-27 (GHS 1)

#### CERCLA (Comprehensive Environmental Response, Compensation, and Liability Act)

Section 102(A) Hazardous Substances (40 CFR 302.4)

#### Clean Air Act

#### 15.1.2. Drug precursors, Controlled Substances Act (21 5 U.S.C. § 802)

Industry or sector specific available guidance(s) NPCA-HMIS® III

Hazardous Materials Identification System (American Coatings Association)

Category	Rating	Description	
Chronic	*	Chronic (long-term) health effects may result from repeated overexposure.	
Health	1	Irritation or minor reversible injury possible.	
Flammability	2	Material that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur.	
Physical hazard         0         Material that is normally stable, even under fire conditions, and will not react with water, pol decompose, condense, or self-react. Non-explosive.		Material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive.	
Personal protective equipment	-		

#### NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States)

Category	Degree of hazard	Description
Flammability	2	Material that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur.
Health	1	Material that, under emergency conditions, can cause significant irritation.
Instability	0	Material that is normally stable, even under fire conditions.
Special hazard		

#### Right to Know Hazardous Substance List Proposition 65 List of chemicals

none of the ingredients are listed

#### Relevant European Union (EU) safety, health and environmental provisions

Classification according to GHS (1272/2008/EC, CLP)		
Hazard class	Category	Hazard class and category
flammable liquid	3	(Flam. Liq. 3)
acute toxicity (oral)	4	(Acute Tox. 4)
reproductive toxicity	2	(Repr. 2)
hazardous to the aquatic environment - chronic hazard	3	(Aquatic Chronic 3)



acc. to OSHA, Appendix D to § 1910.1200

## Jade Ceramic Sealant - Marine

Version number: GHS 2.0 Replaces version of: 2016-05-27 (GHS 1)

### SECTION 16: Other information, including date of preparation or last revision

#### 16.1 Indication of changes (revised safety data sheet)

	Former entry (text/value)	Actual entry (text/value)	Safety- relevant
1.2	Uses advised against: do not use for squirting or spraying do not use for products which come into direct contact with the skin		yes
2.1		Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200): change in the listing (table)	yes
2.1	The most important adverse physicochemical, human health and environmental effects: Skin corrosion produces an irreversible damage to the skin; namely, visible necrosis through the epidermis and into the dermis. The product is combustible and can be ignited by potential ignition sources.	The most important adverse physicochemical, human health and environmental effects: The product is combustible and can be ignited by poten- tial ignition sources.	yes
2.2	Signal word: danger	Signal word: warning	yes
2.2		Pictograms: change in the listing (table)	yes
2.2		Hazard statements: change in the listing (table)	yes
2.2		Precautionary statements - prevention: change in the listing (table)	yes
2.2		Precautionary statements - response: change in the listing (table)	yes
2.2	Hazardous ingredients for labelling: organic polysilazane compound, octamethylcyclotet- rasiloxane	Hazardous ingredients for labelling: octamethylcyclotetrasiloxane, organic polysilazane com- pound	yes
4.1	Following inhalation: In case of respiratory tract irritation, consult a physician. Provide fresh air.	Following inhalation: Provide fresh air.	yes
11.1	Skin corrosion/irritation: Causes severe skin burns and eye damage.	Skin corrosion/irritation: Shall not be classified as corrosive/irritant to skin.	yes
11.1	Serious eye damage/eye irritation: Causes serious eye damage.	Serious eye damage/eye irritation: Shall not be classified as seriously damaging to the eye or eye irritant.	yes
14.1	UN number: 2920	UN number: 1993	yes
14.2	UN proper shipping name: Corrosive liquid, flammable, n.o.s.	UN proper shipping name: Flammable liquid, n.o.s.	yes
14.3	Class: 8 (corrosive substances)	Class: 3 (flammable liquids)	yes
14.3	Subsidiary risk(s): 3 (flammability)		yes
14.4	Packing group: II (substance presenting medium danger)	Packing group: III (substance presenting low danger)	yes
14.7	Index number: 2920	Index number: 1993	yes



Version number: GHS 2.0 Replaces version of: 2016-05-27 (GHS 1)

# Safety Data Sheet acc. to OSHA, Appendix D to § 1910.1200

## Jade Ceramic Sealant - Marine

Section	Former entry (text/value)	Actual entry (text/value)	Safety releva
14.7	Proper shipping name: Corrosive liquid, flammable, n.o.s.	Proper shipping name: Flammable liquid, n.o.s.	yes
14.7	Class: 8	Class: 3	yes
14.7	Packing group: II	Packing group: III	yes
14.7	Danger label(s): 8+3	Danger label(s): 3	yes
14.7		Danger label(s): change in the listing (table)	yes
14.7	Special provisions (SP): B2, IB2, T11, TP2, TP27	Special provisions (SP): B1, B52, IB3, T4, TP1, TP29	yes
14.7	ERG No: 132	ERG No: 128	yes
14.7	UN number: 2920	UN number: 1993	yes
14.7	Proper shipping name: CORROSIVE LIQUID, FLAMMABLE, N.O.S.	Proper shipping name: FLAMMABLE LIQUID, N.O.S.	yes
14.7	Class: 8	Class: 3	yes
14.7	Subsidiary risk(s): 3		yes
14.7	Packing group:	Packing group: III	yes
14.7	Danger label(s): 8+3	Danger label(s): 3	yes
14.7		Danger label(s): change in the listing (table)	yes
14.7	Special provisions (SP): 274	Special provisions (SP): 223, 274, 955	yes
14.7	Excepted quantities (EQ): E2	Excepted quantities (EQ): E1	yes
14.7	Limited quantities (LQ): 1 L	Limited quantities (LQ): 5 L	yes
14.7	EmS: F-E, S-C	EmS: F-E, S-E	yes
14.7	Stowage category: C	Stowage category: A	yes
14.7	UN number: 2920	UN number: 1993	yes
14.7	Proper shipping name: Corrosive liquid, flammable, n.o.s.	Proper shipping name: Flammable liquid, n.o.s.	yes
14.7	Class: 8	Class: 3	yes
14.7	Subsidiary risk(s):		yes



# Safety Data Sheet acc. to OSHA, Appendix D to § 1910.1200

## Jade Ceramic Sealant - Marine

revision: 2016-10-26

Version number: GHS 2.0 Replaces version of: 2016-05-27 (GHS 1)

Section	Former entry (text/value)	Actual entry (text/value)	Safety- relevant
14.7	Packing group: II	Packing group: III	yes
14.7	Danger label(s): 8+3	Danger label(s): 3	yes
14.7		Danger label(s): change in the listing (table)	yes
14.7	Special provisions (SP): 274	Special provisions (SP): A3, 274	yes
14.7	Excepted quantities (EQ): E2	Excepted quantities (EQ): E1	yes
14.7	Limited quantities (LQ): 0,5 L	Limited quantities (LQ): 10 L	yes
15.1		Section 102(A) Hazardous Substances (40 CFR 302.4): none of the ingredients are listed	yes
15.1		Clean Air Act: none of the ingredients are listed	yes
15.1.2.5		Drug precursors, Controlled Substances Act (21 U.S.C. § 802): none of the ingredients are listed	yes
15.1.2.5		NPCA-HMIS® III: change in the listing (table)	yes
15.1.2.5		NFPA® 704: change in the listing (table)	yes
15.1.2.5		Classification according to GHS (1272/2008/EC, CLP): change in the listing (table)	yes

#### 16.2 Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
49 CFR US DOT	49 CFR § 40 U.S. Department of Transportation
Acute Tox.	acute toxicity
ATE	Acute Toxicity Estimate
BCF	BioConcentration Factor
BOD	Biochemical Oxygen Demand
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
CLP	Regulation (EC) No 1272/2008 on classification, labeling and packaging of substances and mixtures
CMR	Carcinogenic, Mutagenic or toxic for Reproduction
COD	chemical oxygen demand
DGR	Dangerous Goods Regulations (see IATA/DGR)
DMEL	Derived Minimal Effect Level
DNEL	Derived No-Effect Level
DOT	Department of Transportation (USA)
EmS	Emergency Schedule



acc. to OSHA, Appendix D to § 1910.1200

## **Jade Ceramic Sealant - Marine**

revision: 2016-10-26

Version number: GHS 2.0 Replaces version of: 2016-05-27 (GHS 1)

Abbr.	Descriptions of used abbreviations
ERG No	Emergency Response Guidebook - Number
Eye Dam.	seriously damaging to the eye
Eye Irrit.	irritant to the eye
Flam. Liq.	flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IARC Monographs	IARC Monographs on the Evaluation of Carcinogenic Risks to Humans
ΙΑΤΑ	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code
log KOW	n-octanol/water
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")
NFPA® 704	National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States)
NPCA-HMIS® III	National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition
OSHA	Occupational Safety and Health Administration (United States)
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
Repr.	reproductive toxicity
Skin Corr.	corrosive to skin
Skin Irrit.	irritant to skin
vPvB	very Persistent and very Bioaccumulative

#### 16.3 Key literature references and sources for data

- OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200 49 CFR § 172.101 Hazardous Materials Table (DOT) -
- \_

#### **Classification procedure** 16.4

Physical and chemical properties: The classification is based on tested mixture. Health hazards/Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

#### 16.5

#### List of relevant phrases (code and full text as stated in chapter 2 and 3)

Code	Text
H224	extremely flammable liquid and vapor
H225	highly flammable liquid and vapor
H226	flammable liquid and vapor
H227	combustible liquid



acc. to OSHA, Appendix D to § 1910.1200

## Jade Ceramic Sealant - Marine

revision: 2016-10-26

Version number: GHS 2.0 Replaces version of: 2016-05-27 (GHS 1)

Code	Text
H302	harmful if swallowed
H314	causes severe skin burns and eye damage
H318	causes serious eye damage
H361f	suspected of damaging fertility

#### 16.7

#### Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.