

Issuing date 27-Oct-2016

Revision Date 27-Oct-2016

Version 2.01

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product name MS-1028 RUBBER SEAL

Recommended use of the chemical and restrictions on use

Product code F00132

Product Type Highly flammable aerosol
Synonyms None

Supplier's details

Recommended Use Undercoating.
Uses advised against No information available

Manufactured For:
Mark Supply, Inc.
P.O. Box 1451
Venice, FL 34285

Emergency telephone number
Chemical Emergency Phone Number INFOTRAC: 800-535-5053
Company Emergency Phone Number 1-941-485-8199

IF ON SKIN: Wash with plenty of soap and water.
 Take off contaminated clothing and wash it before reuse
 If skin irritation occurs: Get medical advice/attention
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 Call a POISON CENTER or doctor/physician if you feel unwell
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
 Do NOT induce vomiting

Precautionary Statements - Storage

Store locked up
 Store in a well-ventilated place. Keep container tightly closed
 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

None

Other information

• Toxic to aquatic life with long lasting effects

0.000003% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

| Chemical Name | CAS-No | Weight %* |
|----------------------------|------------|-----------|
| CALCIUM CARBONATE | 1317-65-3 | 30-40 |
| PROPANE/ISOBUTANE/N-BUTANE | 68476-86-8 | 10-20 |
| TOLUENE | 108-88-3 | 10-20 |
| METHYL ACETATE | 79-20-9 | 10-20 |
| ACETONE | 67-64-1 | 1-10 |
| SOLVENT NAPHTHA | 64742-94-5 | 0.1-1 |
| XYLENE | 1330-20-7 | 0.1-1 |
| CARBON BLACK | 1333-86-4 | 0.1-1 |
| PETROLEUM DISTILLATES | 64742-89-8 | 0.1-1 |

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

First aid measures for different exposure routes

| | |
|---------------------|---|
| Eye contact | Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. If symptoms persist, call a physician. |
| Skin contact | Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician. |
| Inhalation | Move to fresh air. If breathing is difficult, give oxygen. Artificial respiration and/or oxygen may be necessary. If breathing has stopped, contact emergency medical services immediately. |
| Ingestion | Rinse mouth. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Drink plenty of water. Call a physician or Poison Control Center immediately. |

Most important symptoms/effects, acute and delayed

Main Symptoms Causes serious eye irritation. May causes skin irritation. Suspected of causing cancer. Harmful if inhaled.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES**Suitable Extinguishing Media**

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media Decomposition by contact with water may generate vapors which can be ignited by heat or open flame.

Specific hazards arising from the chemical**Explosion Data**

Sensitivity to Mechanical Impact none.

Sensitivity to Static Discharge none.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES**Personal precautions, protective equipment and emergency procedures**

Personal precautions Absorb with sand ,clay, or other suitable material. Hard surfaces may be mopped with water. Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. Avoid dust formation. Remove all sources of ignition. Keep people away from and upwind of spill/leak. Take precautionary measures against static discharges.

Environmental precautions

Environmental precautions Vapors can accumulate in low areas. Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. Should not be released into the environment.

Methods and materials for containment and cleaning up

Methods for Containment Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Pick up and transfer to properly labeled containers. Soak up with inert absorbent material. Clean contaminated surface thoroughly. After cleaning, flush away traces with water. Prevent product from entering drains. Take precautionary measures against static discharges.

7. HANDLING AND STORAGE**Precautions for safe handling**

Advice on safe handling Wear personal protective equipment. Keep away from open flames, hot surfaces and sources of ignition. Avoid inhaling vapors or spray mists. Keep away from direct sun exposure and temperatures over 120 °F (49 °C). Do not puncture, incinerate, or dispose of in household trash compactor.

Conditions for safe storage, including any incompatibilities

Technical measures/Storage conditions Keep containers tightly closed in a dry, cool and well-ventilated place.

Incompatible products Store away from strong acids, alkalis, oxidizing agents.

Aerosol Level 2

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

| Chemical Name | ACGIH TLV | OSHA PEL | NIOSH IDLH |
|--|---|---|--|
| CALCIUM CARBONATE 1317-65-3 | - | TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 15 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction | TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust |
| PROPANE/ISOBUTANE/N-BUTANE 68476-86-8 | 74-98-6: TWA: 1000 ppm 106-97-8: STEL: 1000 ppm 75-28-5: STEL: 1000 ppm | 74-98-6: TWA: 1000 ppm TWA: 1800 mg/m ³ (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m ³ 106-97-8: (vacated) TWA: 800 ppm (vacated) TWA: 1900 mg/m ³ | 74-98-6: IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m ³ 106-97-8: TWA: 800 ppm TWA: 1900 mg/m ³ 75-28-5: TWA: 800 ppm TWA: 1900 mg/m ³ |
| TOLUENE 108-88-3 | TWA: 20 ppm | TWA: 200 ppm (vacated) TWA: 100 ppm (vacated) TWA: 375 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 560 mg/m ³ Ceiling: 300 ppm | IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m ³ STEL: 150 ppm STEL: 560 mg/m ³ |
| METHYL ACETATE 79-20-9 | STEL: 250 ppm TWA: 200 ppm | TWA: 200 ppm TWA: 610 mg/m ³ (vacated) TWA: 200 ppm (vacated) TWA: 610 mg/m ³ (vacated) STEL: 250 ppm (vacated) STEL: 760 mg/m ³ | IDLH: 3100 ppm TWA: 200 ppm TWA: 610 mg/m ³ STEL: 250 ppm STEL: 760 mg/m ³ |
| ACETONE 67-64-1 | STEL: 500 ppm TWA: 250 ppm | TWA: 1000 ppm TWA: 2400 mg/m ³ (vacated) TWA: 750 ppm (vacated) TWA: 1800 mg/m ³ (vacated) STEL: 2400 mg/m ³ The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors (vacated) STEL: 1000 ppm | IDLH: 2500 ppm TWA: 250 ppm TWA: 590 mg/m ³ |
| XYLENE 1330-20-7 | STEL: 150 ppm TWA: 100 ppm | TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m ³ | - |
| CARBON BLACK 1333-86-4 | TWA: 3 mg/m ³ inhalable fraction | TWA: 3.5 mg/m ³ (vacated) TWA: 3.5 mg/m ³ | IDLH: 1750 mg/m ³ TWA: 3.5 mg/m ³ TWA: 0.1 mg/m ³ Carbon black in presence of Polycyclic aromatic hydrocarbons PAH |

ACGIH: (American Conference of Governmental Industrial Hygienists)

OSHA: (Occupational Safety & Health Administration)

NIOSH IDLH: Immediately Dangerous to Life or Health

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Exposure controls

Engineering Measures Showers
Eyewash stations
Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/Face Protection Safety glasses with side-shields.

Skin and body protection Chemical resistant apron. Protective gloves.

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

Hygiene measures Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and chemical properties

| | | | |
|-----------------------|---------|-----------------------|---------|
| Physical state | Aerosol | Odor | Solvent |
| Appearance | opaque | Odor Threshold | |
| Color | black | | |

| <u>Property</u> | <u>Values</u> | <u>Remarks • Methods</u> |
|---|--------------------------|--------------------------|
| pH | No information available | |
| Melting/freezing point | No information available | |
| Boiling point/boiling range | | |
| Flash Point | -104.4 °C / -156 °F | Based on propellant |
| Evaporation rate | No information available | |
| Flammability (solid, gas) | No information available | |
| Flammability Limits in Air | | |
| upper flammability limit | | |
| lower flammability limit | | |
| Vapor pressure | | |
| Vapor density | | |
| Specific Gravity | 1.127 | |
| Water solubility | Practically insoluble | |
| Partition coefficient: n-octanol/water | | |
| Autoignition temperature | No information available | |
| Decomposition temperature | | |
| Viscosity | No information available | |
| Explosive properties | | |

Other information

VOC Content(%) 37.56

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to Avoid

Extremes of temperature and direct sunlight.

Incompatible Materials

Store away from strong acids, alkalis, oxidizing agents.

Hazardous Decomposition Products

None known based on information supplied.

| |
|--------------------------------------|
| 11. TOXICOLOGICAL INFORMATION |
|--------------------------------------|

Information on likely routes of exposure**Product Information**

| | |
|---------------------|--|
| Inhalation | Vapors may irritate throat and respiratory system. May cause respiratory irritation; or may cause drowsiness or dizziness. May cause irritation of respiratory tract. Avoid inhaling vapors or mists. |
| Eye contact | Irritating to eyes. Irritating to eyes . |
| Skin contact | May cause an allergic reaction with skin if in direct contact. Repeated exposure may cause skin dryness or cracking. May cause skin irritation and causes serious eye irritation. May be fatal if swallowed and enters airways. Suspected causing cancer. Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure. May cause respiratory irritation; or may cause drowsiness or dizziness. Avoid contact with skin. |
| Ingestion | May be fatal if swallowed and enters airways. Aspiration into the lungs during swallowing may be harmful. |

Component Information

| Chemical Name | LD50 Oral | LD50 Dermal | LC50 Inhalation |
|-------------------------------------|-----------------------|--------------------------|---------------------------------------|
| TOLUENE 108-88-3 | = 2600 mg/kg (Rat) | = 12000 mg/kg (Rabbit) | = 12.5 mg/L (Rat) 4 h |
| METHYL ACETATE 79-20-9 | > 5 g/kg (Rat) | > 5 g/kg (Rabbit) | = 16000 ppm (Rat) 4 h |
| ACETONE 67-64-1 | = 5800 mg/kg (Rat) | - | = 50100 mg/m ³ (Rat) 8 h |
| SOLVENT NAPHTHA 64742-94-5 | > 5000 mg/kg (Rat) | > 2 mL/kg (Rabbit) | > 590 mg/m ³ (Rat) 4 h |
| XYLENE 1330-20-7 | = 3500 mg/kg (Rat) | > 4350 mg/kg (Rabbit) | = 29.08 mg/L (Rat) 4 h |
| CARBON BLACK 1333-86-4 | > 15400 mg/kg (Rat) | - | - |
| PETROLEUM DISTILLATES 64742-89-8 | - | = 3000 mg/kg (Rabbit) | - |

Information on toxicological effects**Symptoms**

Causes skin, eye, and respiratory irritation. Allergic reaction may occur if in contact with skin. Aspiration into the lungs during swallowing may cause serious lung damage which may be fatal.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization None known.
Germ Cell Mutagenicity Not acutely toxic. May be harmful if swallowed.
Carcinogenicity The table below indicates whether each agency has evaluated a listed ingredient as a carcinogen.

| Chemical Name | ACGIH | IARC | NTP | OSHA |
|---------------------------|-------|----------|-----|------|
| CARBON BLACK 1333-86-4 | A3 | Group 2B | - | - |

ACGIH: (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC: (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

OSHA: (Occupational Safety & Health Administration)

X - Present

Reproductive toxicity Product is or contains a chemical which is a known or suspected reproductive hazard.
Specific target organ systemic toxicity (single exposure) May cause respiratory irritation. May cause drowsiness and dizziness.

Specific target organ systemic toxicity (repeated exposure) Causes damage to Target Organs.

Chronic toxicity May cause adverse liver effects.

Target Organ Effects Central Nervous System, Peripheral Nervous System, Eyes, Kidney, Liver, Lungs, Respiratory System, Skin, Blood, and Hematopoietic System) through prolonged or repeated exposure, Central Nervous System, Eyes, Kidney, Liver, Peripheral Nervous System, Respiratory System, Skin, Central Vascular System, and Lungs, Central Nervous System, Peripheral Nervous System, Eyes, Kidney, Liver, Lungs, Respiratory System, Skin, Blood, and Hematopoietic System, through prolonged or repeated exposure, Central Nervous System, Peripheral Nervous System, Eyes, Kidney, Liver, Lungs, Respiratory System, Skin, Blood, and Hematopoietic System through prolonged or repeated exposure, Central Nervous System, Peripheral Nervous System, Eyes, Kidney, Liver, Lungs, Respiratory System, Skin, Blood and Hematopoietic System, Central Nervous System, Peripheral Nervous System, Eyes, Kidney, Liver, Lungs, Respiratory System, Skin, Blood and Hematopoietic System.

Aspiration hazard May be toxic if swallowed and enters airways.

Numerical measures of toxicity - Product Information

Unknown Acute Toxicity 0.000003% of the mixture consists of ingredient(s) of unknown toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 11650 mg/kg

ATEmix (dermal) 10385 mg/kg

ATEmix (inhalation-dust/mist) 58.4 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

| Chemical Name | Toxicity to algae | Toxicity to fish | Toxicity to microorganisms | Toxicity to daphnia and other aquatic invertebrates |
|---------------|-------------------|------------------|----------------------------|---|
|---------------|-------------------|------------------|----------------------------|---|

| | | | | |
|-------------------------------------|---|--|---|---|
| TOLUENE 108-88-3 | 433 mg/L EC50 Pseudokirchneriella subcapitata 96h 12.5 mg/L EC50 Pseudokirchneriella subcapitata 72h static | 15.22 - 19.05 mg/L LC50 Pimephales promelas 96h flow-through 12.6 mg/L LC50 Pimephales promelas 96h static 5.89 - 7.81 mg/L LC50 Oncorhynchus mykiss 96h flow-through 14.1 - 17.16 mg/L LC50 Oncorhynchus mykiss 96h static 5.8 mg/L LC50 Oncorhynchus mykiss 96h semi-static 11.0 - 15.0 mg/L LC50 Lepomis macrochirus 96h static 54 mg/L LC50 Oryzias latipes 96h static 28.2 mg/L LC50 Poecilia reticulata 96h semi-static 50.87 - 70.34 mg/L LC50 Poecilia reticulata 96h static | - | 5.46 - 9.83 mg/L EC50 Daphnia magna 48h Static 11.5 mg/L EC50 Daphnia magna 48h |
| METHYL ACETATE 79-20-9 | 120 mg/L EC50 Desmodesmus subspicatus 72h | 295 - 348 mg/L LC50 Pimephales promelas 96h flow-through 250 - 350 mg/L LC50 Brachydanio rerio 96h static | - | 1026.7 mg/L EC50 Daphnia magna 48h |
| ACETONE 67-64-1 | - | 4.74 - 6.33 mL/L LC50 Oncorhynchus mykiss 96h 6210 - 8120 mg/L LC50 Pimephales promelas 96h static 8300 mg/L LC50 Lepomis macrochirus 96h | - | 10294 - 17704 mg/L EC50 Daphnia magna 48h Static 12600 - 12700 mg/L EC50 Daphnia magna 48h |
| SOLVENT NAPHTHA 64742-94-5 | - | 19 mg/L LC50 Pimephales promelas 96h static 2.34 mg/L LC50 Oncorhynchus mykiss 96h 1740 mg/L LC50 Lepomis macrochirus 96h static 45 mg/L LC50 Pimephales promelas 96h flow-through 41 mg/L LC50 Pimephales promelas 96h | - | 0.95 mg/L EC50 Daphnia magna 48h |
| XYLENE 1330-20-7 | - | 13.4 mg/L LC50 Pimephales promelas 96h flow-through 2.661 - 4.093 mg/L LC50 Oncorhynchus mykiss 96h static 13.5 - 17.3 mg/L LC50 Oncorhynchus mykiss 96h 13.1 - 16.5 mg/L LC50 Lepomis macrochirus 96h flow-through 19 mg/L LC50 Lepomis macrochirus 96h 7.711 - 9.591 mg/L LC50 Lepomis macrochirus 96h static 23.53 - 29.97 mg/L LC50 Pimephales promelas 96h static 780 mg/L LC50 Cyprinus carpio 96h semi-static 780 mg/L LC50 Cyprinus carpio 96h 30.26 - 40.75 mg/L LC50 Poecilia reticulata 96h static | - | 3.82 mg/L EC50 water flea 48h 0.6 mg/L LC50 Gammarus lacustris 48h |
| PETROLEUM DISTILLATES 64742-89-8 | 4700 mg/L EC50 Pseudokirchneriella subcapitata 72h | - | - | - |

Persistence and degradability

.

Bioaccumulation

.

| Chemical Name | log Pow |
|--|-------------|
| PROPANE/ISOBUTANE/N-BUTANE 68476-86-8 | <=2.8 |
| TOLUENE 108-88-3 | 2.7 |
| METHYL ACETATE 79-20-9 | 0.18 |
| ACETONE 67-64-1 | -0.24 |
| SOLVENT NAPHTHA 64742-94-5 | 2.9 - 6.1 |
| XYLENE 1330-20-7 | 2.77 - 3.15 |

Other adverse effects No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment

Waste Disposal Methods This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261). Dispose of in accordance with federal, state, and local regulations.

Contaminated packaging Do not re-use empty containers.

14. TRANSPORT INFORMATION

DOT Ground CONSUMER COMMODITY ORM-D
or
LIMITED QUANTITY

IATA UN1950, AEROSOLS, FLAMMABLE, 2.1, LTD. QTY.

IMDG UN1950, AEROSOLS, FLAMMABLE, 2.1, LTD. QTY.

15. REGULATORY INFORMATION

International Inventories

| Chemical Name | TSCA | DSL/NDSL | EINECS/ELI NCS | ENCS | IECSC | KECL | PICCS | AICS |
|--------------------------------|------|----------|-------------------|------------|-------|------|-------|------|
| CALCIUM CARBONATE | X | X | X | X | X | X | X | X |
| PROPANE/ISOBUTA NE/N-BUTANE | X | X | X | Not listed | X | X | X | X |
| TOLUENE | X | X | X | X | X | X | X | X |
| METHYL ACETATE | X | X | X | X | X | X | X | X |
| ACETONE | X | X | X | X | X | X | X | X |
| SOLVENT NAPHTHA | X | X | X | X | X | X | X | X |
| XYLENE | X | X | X | X | X | X | X | X |
| CARBON BLACK | X | X | X | X | X | X | X | X |
| PETROLEUM DISTILLATES | X | X | X | Not listed | X | X | X | X |

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

CHINA - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

U.S. Federal Regulations**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does contain a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

| Chemical Name | CAS-No | Weight %* | SARA 313 - Threshold Values % |
|--------------------|----------|-----------|-------------------------------|
| TOLUENE - 108-88-3 | 108-88-3 | 16.9191 | 1.0 |

SARA 311/312 Hazard Categories

| | |
|-----------------------------------|-----|
| Acute Health Hazard | Yes |
| Chronic Health Star Hazard | Yes |
| Fire Hazard | Yes |
| Sudden Release of Pressure Hazard | Yes |
| Reactive Hazard | no |

Clean Water Act

This product does contain the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

| Chemical Name | CWA - Reportable Quantities | CWA - Toxic Pollutants | CWA - Priority Pollutants | CWA - Hazardous Substances |
|---------------------|-----------------------------|------------------------|---------------------------|----------------------------|
| TOLUENE 108-88-3 | 1000 lb | X | X | X |
| XYLENE 1330-20-7 | 100 lb | | | X |

CERCLA

This material, as supplied, does contain substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

| Chemical Name | Hazardous Substances RQs | Extremely Hazardous Substances RQs | RQ |
|---------------------|--------------------------|------------------------------------|--|
| TOLUENE 108-88-3 | 1000 lb 1 lb | | RQ 1000 lb final RQ RQ 454 kg final RQ RQ 1 lb final RQ RQ 0.454 kg final RQ |
| ACETONE 67-64-1 | 5000 lb | | RQ 5000 lb final RQ RQ 2270 kg final RQ |
| XYLENE 1330-20-7 | 100 lb | | RQ 100 lb final RQ RQ 45.4 kg final RQ |

U.S. State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals:

| Chemical Name | California Prop. 65 |
|--------------------------|---------------------|
| TOLUENE - 108-88-3 | Developmental |
| METHANOL - 67-56-1 | Developmental |
| CARBON BLACK - 1333-86-4 | Cancer |

U.S. State Right-to-Know Regulations

| Chemical Name | New Jersey | Massachusetts | Pennsylvania |
|-------------------------------------|------------|---------------|--------------|
| CALCIUM CARBONATE 1317-65-3 | X | X | X |
| TOLUENE 108-88-3 | X | X | X |
| METHYL ACETATE 79-20-9 | X | X | X |
| ACETONE 67-64-1 | X | X | X |
| XYLENE 1330-20-7 | X | X | X |
| CARBON BLACK 1333-86-4 | X | X | X |
| PETROLEUM DISTILLATES 64742-89-8 | | | X |

EPA Pesticide Registration Number Not applicable

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all the information required by the CPR.

16. OTHER INFORMATION

| | | | | |
|-----------------------------------|-------------------------|--|--------------------------|--|
| NFPA | Health Hazard 2 | Flammability 4 | Instability 1 | Physical and chemical hazards - |
| HMIS | Health Hazard 2* | Flammability 4 | Physical Hazard 1 | Personal protection B |
| <i>Chronic Hazard Star Legend</i> | | <i>Chronic Health Star Hazard Repeated or prolonged exposure may cause central nervous system damage</i> | | |

Issuing date 27-Oct-2016 27-
 Revision Date Oct-2016
 Revision Note

Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet