Issuing date 11-Sep-2018

Revision Date 30-Jan-2020

Version 1.03

SAFETY DATA SHEET.

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

<u>Product identifier</u> Product name	MS-1003 SUPER SOLV
Recommended use of the chemical and restrictions on use	
Product code	F00133
<u>Product Type</u> Synonyms	Chlorinated aerosol Extremely Flammable Aerosol None
Supplier's details	
Recommended Use	Carburetor cleaner.
Uses advised against	This chemical/product is not and cannot be distributed in commerce (as defined inTSCA section 3(5)) or processed (as defined in TSCA section 3(13)) for consumerpaint or coating removal. See Section: 15
Manufactured For: Mark Supply, Inc. P.O. Box 1451 Venice, FL 34285 1-941-485-8199	Manufacturer American Jetway Corporation 34136 Myrtle Street Wayne, MI 48184-0126 Phone:(734) 721-5930
Emergency telephone number Chemical Emergency Phone Number	CHEMTREC : 1-800-424-9300
Company Emergency Phone	

2. HAZARDS IDENTIFICATION

Classification

DANGER

Acute Toxicity - Oral	Category 4
Acute Toxicity - Dermal	Category 4
Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Germ cell mutagenicity	Category 2
Carcinogenicity	Category 1A
Reproductive Toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 1
Flammable Aerosols	Category 1
Gases under pressure	Compressed Gas

GHS Label elements, including precautionary statements

Emergency Overview

Hazard Statements Harmful if swallowed Harmful in contact with skin Harmful in contact with skin Harmful if inhaled Causes skin irritation. Causes serious eye irritation. Suspected of causing genetic defects Suspected of causing cancer. Suspected of damaging fertility or the unborn child Causes damage to organs (Eyes, Skin, Respiratory System, Central Nervous System and Gastrointestinal Tract). Extremely Flammable Aerosol Contains gas under pressure; may explode if heated

Appearance Clear

Physical state Aerosol

Odor Solvent

Precautionary Statements - Prevention

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing,eye protection,face protection. Wash face, hands and any exposed skin thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Do not breathe dust, fume, gas, mist, vapors, spray. Keep away from heat, sparks, open flames, hot surfaces - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

Precautionary Statements - Response

Specific measures (see first aid on this label)

Specific treatment (see first aid on this label). IF EXPOSED: Call a POISON CENTER or doctor/physician IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice, attention IF ON SKIN: Wash with plenty of soap and water. Call a POISON CENTER or doctor, physician if you feel unwell. Take off contaminated clothing and wash it before reuse. IF INHALED : Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor, physician if you feel unwell. If SWALLOWED :Call a POISON CENTER or doctor, physician if you feel unwell. Rinse mouth

Precautionary Statements - Storage

Store locked up. Protect from sunlight. Store in a well-ventilated place Do not expose to temperatures exceeding 122°F (50°C)

Precautionary Statements - Disposal

Dispose of contents, container to an approved waste disposal plant.

Hazards not otherwise classified (HNOC)

None

Other information

0% of the mixture consists of ingredient(s) of unknown toxicity.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %*
XYLENE	1330-20-7	30-40
DICHLOROMETHANE	75-09-2	20-30
PROPANE/ISOBUTANE/N-BUTANE	68476-86-8	20-30
METHANOL	67-56-1	10-20
ISOPROPYL ALCOHOL	67-63-0	1-10
TOLUENE	108-88-3	<1
PROPYLENE OXIDE	75-56-9	<1

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

First aid measures for different exposure routes

General advice	Avoid contact with eyes, skin, and clothing. Avoid breathing vapors, mist, or gas.
Eye contact	Immediately flush with plenty of water for at least 15 minutes. After initial flushing, remove any contact lenses and continue flushing. If eye irritation persists, consult a doctor.
Skin contact	Wash off with soap and plenty of water. Remove and wash contaminated clothing before re-use. If skin irritation persists, call a physician.
Inhalation	Move to fresh air. If not breathing, give artificial respiration. If breathing has stopped, contact emergency medical services immediately.
Ingestion	Call a physician or Poison Control Center immediately. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Risk of product entering the lungs on

	vomiting after ingestion.
Protection of First-aiders	Remove all sources of ignition.
Most important symptoms/effects,	acute and delayed
Main Symptoms	Harmful if swallowed. Harmful in contact with skin. Harmful if inhaled. Causes skin and serious eye irritation. Suspected of causing genetic defects. Suspected of causing cancer. Suspected of damaging fertility or the unborn child. Causes damage to organs.
Indication of immediate medical att	ention and special treatment needed, if necessary
Notes to physician	Do not administer adrenaline or epinephrine to a victim of chlorinated solvent poisoning. Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Water fog.Dry chemical. Foam. Carbon dioxide (CO2). Cool containers/tanks with water spray.

veniting often in conting

Unsuitable Extinguishing Media Do not use a solid water stream as it may scatter and spread fire. Keep away from sources of ignition - No smoking.

Specific hazards arising from the chemical

Extremely Flammable / Flammable. The product causes burns of eyes, skin and mucous membranes. Flash back possible over considerable distance. In the event of fire and/or explosion do not breathe fumes. Keep product and empty container away from heat and sources of ignition.

Hazardous Combustion
ProductsCarbon oxides , Hydrocarbons, Fumes. Chlorine gas. Halogenated compounds. Acrid
smoke/fumes. Sulfur oxides.

Explosion Data Sensitivity to Mechanical Impact none. Sensitivity to Static Discharge Yes.

Protective Equipment and Precautions for Firefighters

In the event of fire and/or explosion do not breathe fumes. As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Use shielding to protect fire-fighters from bursting containers.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions	Use with adequate ventiliation to keep the exposure levels below the OELS. Follow safe handling advice and personal protective equipment recommendations.			
Environmental precautions				
Environmental precautions	Vapors can accumulate in low areas. Report spills as required by local and federal regulations. Do not allow material to contaminate ground water system. Do not flush into surface water or sanitary sewer system. Should not be released into the environment.			
Methods and materials for containment and cleaning up				
Methods for Containment	Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent product from entering drains.			
Methods for cleaning up	Soak up with inert absorbent material. Contain liquid and collect with an inter, non-combustible material. Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly . After cleaning, flush away traces with water. Prevent			

product from entering drains. Take precautionary measures against static discharges.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling	Avoid breathing vapors or mists. Avoid contact with skin, eyes and clothing. Keep away from open flames, hot surfaces and sources of ignition. Contents under pressure. Do not puncture or incinerate cans. Handle in accordance with good industrial hygiene and safety practice. Take precautionary measures against static discharges.		
Conditions for safe storage, including any incompatibilities			
Technical measures/Storage conditions	Keep container tightly closed in a dry and well-ventilated place. Keep away from open flames, hot surfaces, and sources of ignition. Keep in properly labeled containers. Keep out of the reach of children. Store locked up.		
Incompatible products	Strong acids, alkalis, oxidizing agents.		
Aerosol Level	2		

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Exposure Guidelines			
Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
XYLENE 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m ³	Not Established
DICHLOROMETHANE 75-09-2	TWA: 50 ppm	TWA: 25 ppm (vacated) TWA: 500 ppm (vacated) STEL: 2000 ppm 5 min in any 3 h (vacated) Ceiling: 1000 ppm STEL: 125 ppm see 29 CFR 1910.1052	IDLH: 2300 ppm
PROPANE/ISOBUTANE/N-BUTANE 68476-86-8	74-98-6: TWA: 1000 ppm 106-97-8: STEL: 1000 ppm 75-28-5: STEL: 1000 ppm	74-98-6:TWA: 1000 ppm TWA: 1800 mg/m ³ (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m ³ 106-97-8: (vacated) TWA: 800 ppm (vacated) TWA: 1900 mg/m ³	74-98-6:IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m ³ 106-97-8:TWA: 800 ppm TWA: 1900 mg/m ³ 75-28-5:TWA: 800 ppm TWA: 1900 mg/m ³
METHANOL 67-56-1	STEL: 250 ppm TWA: 200 ppm Skin - potential significant contribution to overall exposure by the cutaneous route	TWA: 200 ppm TWA: 260 mg/m ³ (vacated) TWA: 200 ppm (vacated) TWA: 260 mg/m ³ (vacated) STEL: 250 ppm (vacated) STEL: 325 mg/m ³ (vacated) S*	IDLH: 6000 ppm TWA: 200 ppm TWA: 260 mg/m ³ STEL: 250 ppm STEL: 325 mg/m ³
ISOPROPYL ALCOHOL 67-63-0	STEL: 400 ppm TWA: 200 ppm	TWA: 400 ppm TWA: 980 mg/m ³ (vacated) TWA: 400 ppm (vacated) TWA: 980 mg/m ³ (vacated) STEL: 500 ppm (vacated) STEL: 1225 mg/m ³	IDLH: 2000 ppm TWA: 400 ppm TWA: 980 mg/m ³ STEL: 500 ppm STEL: 1225 mg/m ³
TOLUENE 108-88-3	TWA: 20 ppm	TWA: 200 ppm (vacated) TWA: 100 ppm (vacated) TWA: 375 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 560 mg/m ³	IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m ³ STEL: 150 ppm STEL: 560 mg/m ³

F00133 - MS-1003 SUPER SOLV

Revision Date 30-Jan-2020

		Ceiling: 300 ppm	
PROPYLENE OXIDE 75-56-9	TWA: 2 ppm	TWA: 100 ppm TWA: 240 mg/m ³ (vacated) TWA: 20 ppm (vacated) TWA: 50 mg/m ³	IDLH: 400 ppm
ETHYL BENZENE 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 125 ppm (vacated) STEL: 545 mg/m ³	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m ³ STEL: 125 ppm STEL: 545 mg/m ³

ACGIH: (American Conference of Governmental Industrial Hygienists) OSHA: (Occupational Safety & Health Administration) NIOSH IDLH: Immediately Dangerous to Life or Health

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Exposure controls

Engineering Measures	Ventilation systems. Use adequate ventilation to keep the exposure levels below the
	occupational exposure limits. Showers, eyewash stations, and ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/Face Protection	Safety glasses with side-shields. Tightly fitting safety goggles.
Skin and body protection	Chemical resistant apron. Protective gloves.
Respiratory protection	If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.
Hygiene measures	Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and chemical properties

Physical state Appearance Color	Aerosol Clear Clear	Odor Odor Threshold	Solvent
<u>Property</u> pH Melting/freezing point Boiling point/boiling range	<u>Values</u> No information available No information available	<u>Remarks • Methods</u>	
Flash Point Evaporation rate Flammability (solid, gas) Flammability Limits in Air upper flammability limit lower flammability limit	-97 °C / -143 °F No information available No information available	Based on propellant	
Vapor pressure Vapor density Specific Gravity Water solubility Partition coefficient: n-octanol/wate Autoignition temperature Decomposition temperature	.871 No information available er No information available	Not applicable	
Viscosity Explosive properties	No information available		

Other information

VOC Content(%)

71.8

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to Avoid

Extremes of temperature and direct sunlight.

Incompatible Materials

Strong acids, alkalis, oxidizing agents.

Hazardous Decomposition Products

Carbon oxides , Hydrocarbons, Fumes.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation	Harmful if inhaled.
Eye contact	Causes serious eye irritation.
Skin contact	Causes skin irritation. Harmful in contact with skin.
Ingestion	Harmful and may be fatal if swallowed and enters airways and lungs.

Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
XYLENE	= 3500 mg/kg (Rat)	> 4350 mg/kg (Rabbit)	= 29.08 mg/L (Rat) 4 h
1330-20-7			
DICHLOROMETHANE	= 1600 mg/kg (Rat)	-	= 53 mg/L (Rat) 6 h
75-09-2			
METHANOL	= 6200 mg/kg (Rat)	= 15840 mg/kg (Rabbit)	= 22500 ppm (Rat) 8 h
67-56-1			
ISOPROPYL ALCOHOL	= 1870 mg/kg (Rat)	= 4059 mg/kg (Rabbit)	= 72600 mg/m ³ (Rat) 4 h
67-63-0			
TOLUENE	= 2600 mg/kg (Rat)	= 12000 mg/kg (Rabbit)	= 12.5 mg/L (Rat) 4 h
108-88-3			
PROPYLENE OXIDE	= 520 mg/kg (Rat)	= 1244 mg/kg (Rabbit)	= 9.48 mg/L (Rat) 4 h
75-56-9			

Information on toxicological effects

Symptoms

Harmful if swallowed. Harmful in contact with skin. Harmful if inhaled. Causes skin and serious eye irritation. Suspected of causing genetic defects. Suspected of causing cancer. Suspected of damaging fertility or the unborn child. Causes damage to organs listed below.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Eye damage/irritation		Irritating to sk Irritating to ey	'es.		
Sensitization		Not a known	sensitizer.		
Germ cell mutagenicity		Suspected of	causing genetic defects	5.	
Carcinogenicity		The table below	ow indicates whether ea	ach agency has evaluated a liste	ed ingredient as a
U		carcinogen.			C C
Chemical Name		ACGIH	IARC	NTP	OSHA
XYLENE		-	Group 3	-	
1330-20-7					
DICHLOROMETHANE		A3	Group 2A	Reasonably Anticipated	х
75-09-2		-		,	
TOLUENE		-	Group 3	-	-
108-88-3					
PROPYLENE OXIDE		A3	Group 2B	Reasonably Anticipated	Х
75-56-9		-		,	
ACGIH: (American Con	ference of	Governmental In	dustrial Hygienists)		
A3 - Animal Carcinogen			,		
A2 - Suspected Human C	Carcinogen				
A1 - Known Human Carc	inogen				
IARC: (International Ag		esearch on Cance	er)		
Group 2B - Possibly Card			,		
Group 3 - Not Classifiable			nans		
Group 2A - Probably Car					
Group 1 - Carcinogenic to					
NTP: (National Toxicity	Program)				
Reasonably Anticipated -		ly Anticipated to be	a Human Carcinogen		
Known - Known Carcinog		,,	3		
OSHA: (Occupational S		alth Administratio	on)		
X - Present	, <u>,</u>		,		
Reproductive toxicity		Product is or	contains a chemical wh	ich is a known or suspected rep	roductive hazard.
Specific target organ sys	stemic		age to Target Organs li		
toxicity (single exposure					
Specific target organ sys		No known off	ect based on informatio	n supplied	
		NO KIOWITEI	ect based on informatio	n supplied.	
toxicity (repeated exposi-	ure)				
Chronic toxicity				ncentrating and inhaling content	
				s been associated with irregular	heart rhythms and
		potential card			
Target Organ Effects		Central Nervo	ous System, Gastrointes	stinal Tract, Eyes, Respiratory S	System, and Skin.
Neurological effects		Intentional mi	suse by deliberately co	ncentrating and inhaling content	s may be harmful or
		fatal.	,		
Aspiration hazard		Harmful if swa	allowed		
Aspiration nazaru		riamiu ii Swa	allowed.		
Numerical measures of t	oxicity -	Product Informa	ation		
Unknown Acute Toxicity	,	0% of the mi	xture consists of ingred	ient(s) of unknown toxicity.	
The following values are					
	calculate				
ATEmix (oral)		3045 mg/kg			
ATEmix (dermal)		8235 mg/kg			

ATEmix (definal)b235 mg/kgATEmix (inhalation-gas)250000 mg/lATEmix (inhalation-dust/mist)14.5 mg/lATEmix (inhalation-vapor)2273 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to microorganisms	Toxicity to daphnia and other aquatic invertebrates
XYLENE	-	13.4 mg/L LC50 Pimephales	-	3.82 mg/L EC50 water flea
1330-20-7		promelas 96h flow-through		48h 0.6 mg/L LC50
		2.661 - 4.093 mg/L LC50		Gammarus lacustris 48h
		Oncorhynchus mykiss 96h		
		static 13.5 - 17.3 mg/L LC50		
		Oncorhynchus mykiss 96h		
		13.1 - 16.5 mg/L LC50		

		Lepomis macrochirus 96h		
		flow-through 19 mg/L LC50		
		Lepomis macrochirus 96h		
		7.711 - 9.591 mg/L LC50		
		Lepomis macrochirus 96h		
		static 23.53 - 29.97 mg/L		
		LC50 Pimephales promelas		
		96h static 780 mg/L LC50		
		Cyprinus carpio 96h		
		semi-static 780 mg/L LC50		
		Cyprinus carpio 96h 30.26 -		
		40.75 mg/L LC50 Poecilia		
		reticulata 96h static		
DICHLOROMETHANE	500 mg/L EC50	140.8 - 277.8 mg/L LC50	-	1532 - 1847 mg/L EC50
75-09-2	Pseudokirchneriella	Pimephales promelas 96h		Daphnia magna 48h Static
10 00 2				
	subcapitata 96h 500 mg/L	flow-through 262 - 855 mg/L		190 mg/L EC50 Daphnia
	EC50 Pseudokirchneriella	LC50 Pimephales promelas		magna 48h
	subcapitata 72h	96h static 193 mg/L LC50		°,
	oubouphata / En			
		Lepomis macrochirus 96h		
		static 193 mg/L LC50		
		Lepomis macrochirus 96h		
		flow-through		
		now-unough		
PROPANE/ISOBUTANE/N-	-	-	-	-
BUTANE				
68476-86-8				
		00000		
METHANOL	-	28200 mg/L LC50	-	-
67-56-1		Pimephales promelas 96h		
		flow-through 100 mg/L LC50		
		Pimephales promelas 96h		
		static 19500 - 20700 mg/L		
		LC50 Oncorhynchus mykiss		
		96h flow-through 18 - 20		
		mL/L LC50 Oncorhynchus		
		mykiss 96h static 13500 -		
		17600 mg/L LC50 Lepomis		
		macrochirus 96h		
		flow-through		
ISOPROPYL ALCOHOL	1000 mg/L ECE0	9640 mg/L LC50	-	12200 mg/L ECEO Dophoio
	1000 mg/L EC50		-	13299 mg/L EC50 Daphnia
67-63-0	Desmodesmus subspicatus	Pimephales promelas 96h		magna 48h
	96h 1000 mg/L EC50	flow-through 11130 mg/L		_
	Desmodesmus subspicatus	LC50 Pimephales promelas		
	72h	96h static 1400000 µg/L		
		LC50 Lepomis macrochirus		
		96h		
TOLUENE	400			F 40 0 00 # F0F5
TOLUENE	433 mg/L EC50	15.22 - 19.05 mg/L LC50	-	5.46 - 9.83 mg/L EC50
108-88-3	Pseudokirchneriella	Pimephales promelas 96h		Daphnia magna 48h Static
	subcapitata 96h 12.5 mg/L	flow-through 12.6 mg/L LC50		11.5 mg/L EC50 Daphnia
			1	
	EC50 Pseudokirchneriella	Pimephales promelas 96h		magna 48h
	subcapitata 72h static	static 5.89 - 7.81 mg/L LC50		
		Oncorhynchus mykiss 96h		
		flow-through 14.1 - 17.16		
		mg/L LC50 Oncorhynchus		
		mykiss 96h static 5.8 mg/L		
		LC50 Oncorhynchus mykiss		
		96h semi-static 11.0 - 15.0		
		mg/L LC50 Lepomis		
		macrochirus 96h static 54		
		mg/L LC50 Oryzias latipes		
		96h static 28.2 mg/L LC50		
		Poecilia reticulata 96h		
1				
1	1	semi-static 50.87 - 70.34		
		mall ICEO Dessilia		1
		mg/L LC50 Poecilia		
		0		
	240 mg/L ECE0	reticulata 96h static		250 mall ECEO Donhais
PROPYLENE OXIDE	240 mg/L EC50	reticulata 96h static 215 mg/L LC50 Lepomis	-	350 mg/L EC50 Daphnia
PROPYLENE OXIDE 75-56-9	Pseudokirchneriella	reticulata 96h static	-	350 mg/L EC50 Daphnia magna 48h
		reticulata 96h static 215 mg/L LC50 Lepomis	-	

Persistence and degradability

Bioaccumulation

Chemical I	Name	log Pow
XYLEN	-	3.15
1330-20		4.05
DICHLOROMI 75-09-		1.25
PROPANE/ISOBUTA		2.8
68476-8		2.0
METHAN		-0.77
67-56-	1	
ISOPROPYL A	LCOHOL	0.05
67-63-		
TOLUE		2.7
108-88 PROPYLENE		0.00
75-56-		0.08
75-56-	5	
Other adverse effects	No information available	
	13. DISPOSAL CO	ONSIDERATIONS
Waste treatment		
Waste Disposal Methods	261). Dispose of in accord	is a hazardous waste according to federal regulations (40 CFR ance with federal, state, and local regulations. Dispose of in alations. Dispose of in accordance with federal, state, and local
Contaminated packaging	Do not re-use empty conta	iners.
	14. TRANSPORT	
DOT Ground	CONSUMER COMMODIT	Y ORM-D
	LIMITED QUANTITY	
ΙΑΤΑ	UN1950, AEROSOLS,FLA PACKING GROUP III, 2.1	MMABLE,CONTAINING SUBSTANCE IN DIVISION 6.1, (6.1), ,LTD.QTY.
IMDG	UN1950, AEROSOLS, 2.1	(6.1), LID.QIY.

15. REGULATORY INFORMATION

International Inventories

Chemical Name	TSCA	DSL/NDSL	EINECS/ELI NCS	ENCS	IECSC	KECL	PICCS	AICS
XYLENE	Х	Х	X	Х	Х	Х	Х	Х
DICHLOROMETHANE	Х	Х	Х	Х	Х	Х	Х	Х
PROPANE/ISOBUTA	Х	X	Х	х	Х	Х	Х	Х

F00133 - MS-1003 SUPER SOLV

NE/N-BUTANE								
METHANOL	Х	Х	Х	Х	Х	Х	Х	Х
ISOPROPYL ALCOHOL	Х	Х	Х	Х	Х	Х	Х	Х
TOLUENE	Х	Х	Х	Х	Х	Х	Х	Х
PROPYLENE OXIDE	Х	Х	Х	Х	Х	Х	Х	Х

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

CHINA - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

<u>TSCA</u>

This chemical/product is not and cannot be distributed in commerce (as defined inTSCA section 3(5)) or processed (as defined in TSCA section 3(13)) for consumerpaint or coating removal.

U.S. Federal Regulations

<u>SARA 313</u>

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does contain a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %*	SARA 313 - Threshold Values %
XYLENE - 1330-20-7	1330-20-7	30.4594	1.0
DICHLOROMETHANE - 75-09-2	75-09-2	28.2005	0.1
METHANOL - 67-56-1	67-56-1	16.0861	1.0
ISOPROPYL ALCOHOL - 67-63-0	67-63-0	1.53201	1.0
PROPYLENE OXIDE - 75-56-9	75-56-9	0.14171	0.1

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Star Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	Yes
Reactive Hazard	No

Clean Water Act

This product does contain the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
XYLENE 1330-20-7	100 lb			Х
DICHLOROMETHANE 75-09-2		X	X	
TOLUENE 108-88-3	1000 lb	X	X	Х
PROPYLENE OXIDE 75-56-9	100 lb			Х

CERCLA

This material, as supplied, does contain substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name Hazardous Substances Ness Extremely Hazardous Substances Nes		Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances	RQ
--	--	---------------	--------------------------	--------------------------------	----

F00133 - MS-1003 SUPER SOLV

		RQs	
XYLENE 1330-20-7	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ
DICHLOROMETHANE 75-09-2	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ
METHANOL 67-56-1	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
TOLUENE 108-88-3	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ
PROPYLENE OXIDE 75-56-9	100 lb	100 lb	RQ 100 lb final RQ RQ 45.4 kg final RQ

U.S. State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:



This product can expose you to chemicals including those listed below, which is [are] known to the State of California to cause cancer, birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Chemical Name	California Prop. 65	
DICHLOROMETHANE - 75-09-2	Carcinogen /20-30%	
METHANOL - 67-56-1	Developmental / 10-20%	
TOLUENE - 108-88-3	Developmental/<1%	
PROPYLENE OXIDE - 75-56-9	Carcinogen/ <1%	
ETHYL BENZENE - 100-41-4	Cancer/ <0.1%	

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
XYLENE	Х	Х	Х
1330-20-7			
DICHLOROMETHANE	Х	Х	Х
75-09-2			
METHANOL	Х	Х	Х
67-56-1			
ISOPROPYL ALCOHOL	Х	Х	Х
67-63-0			
TOLUENE	Х	Х	Х
108-88-3			
PROPYLENE OXIDE	Х	Х	X
75-56-9			
ETHYL BENZENE	Х	Х	X
100-41-4			

EPA Pesticide Registration Number Not applicable

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all the information required by the CPR.

Legend NPRI - National Pollutant Release Inventory

16. OTHER INFORMATION							
NFPA_	Health Hazard 2	Flammability 4	Instability 0	Physical and chemica hazards *			
HMIS	Health Hazard 2*	Flammability 4	Physical Hazard 1	Personal protection E			
Chronic Hazard Star Le		Chronic Health Star Hazard Repeated or prolonged exposure may cause central nervous system damage Chlorinated solvents,					
Prepared By		n Jetway Corporation vrtle Street					
		MI 48184-0126					
Issuing date	, ,	11-Sep-2018					
Revision Date	•	30-Jan-2020					
Revision Note							
1 (M)SDS sections up	dated 15 2 3 8 11 12						
Disclaimer							
The information prov	ided on this SDS is corr	aat to the best of our kn	owledge information and	haliaf at the date of ite			

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet