

SAFETY DATA SHEET

1. Identification

Product number	100009594	
Product identifier	MSI TECH-SOLV	
Company information	MARK SUPPLY INC 156 PROGRESS CIRCLE VENICE, FL 34292 United States	
Company phone	General Assistance 941-485-8199	
Emergency telephone US	INFOTRAC 800-535-5053	
Emergency telephone outside US	1-952-852-4646	
Version #	01	
Recommended use	Cleaner	
Recommended restrictions	None known.	

2. Hazard(s) identification

Physical hazards	Flammable aerosols	Category 1
Health hazards	Skin corrosion/irritation	Category 2
	Reproductive toxicity (fertility)	Category 2
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Specific target organ toxicity, repeated exposure	Category 2
	Aspiration hazard	Category 1
OSHA defined hazards	Not classified.	

Label elements



Signal word Hazard statement

Extremely flammable aerosol. May be fatal if swallowed and enters airways. Causes skin irritation. May cause drowsiness or dizziness. Suspected of damaging fertility. May cause damage to organs through prolonged or repeated exposure.

sds Us 1 / 11

Precautionary statement Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe mist or vapor. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.

Response If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin: Wash with plenty of water. If inhaled: Remove person to fresh air and keep comfortable for breathing. If

	exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse.		
Storage	Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.		
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.		
Environmental hazards	Hazardous to the aquatic environment, acute hazard	Category 2	
	Hazardous to the aquatic environment, long-term hazard	Category 2	

Hazard(s) not otherwise	None known.
classified (HNOC)	
Supplemental information	None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Naphtha, (Petroleum), Hydrotreated Light		64742-49-0	40 - 60
n-Hexane		110-54-3	20 - 40
Carbon Dioxide		124-38-9	2.5 - 10
Isopropyl Alcohol		67-63-0	2.5 - 10
Cyclohexane		110-82-7	1 - 2.5
Other components below reportable le	evels		0.01 - 0.1

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
Skin contact	Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Most important symptoms/effects, acute and delayed	Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.
5. Fire-fighting measures	
Suitable extinguishing media	Foam. Powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes

breathe fumes.

General fire hazards

Extremely flammable aerosol.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Product name: 14 OZ MS	SI PRFSSNL TE	CH-SOLV CLNR LB 12PK	SDS US
Product #: 1000009594	Version #: 01	Issue date: 06-23-2016	2 / 11

Methods and materials for containment and cleaning up	Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent entry into waterways, sewer, basements or confined areas. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.
Environmental precautions	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS. Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.
7. Handling and storage	
Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Do not breathe mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Level 3 Aerosol.
including any incompatibilities	Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	
Carbon Dioxide (CAS 124-38-9)	PEL	9000 mg/m3	
,		5000 ppm	
Cyclohexane (CAS 110-82-7)	PEL	1050 mg/m3	
		300 ppm	
Isopropyl Alcohol (CAS 67-63-0)	PEL	980 mg/m3	
,		400 ppm	
n-Hexane (CAS 110-54-3)	PEL	1800 mg/m3	
		500 ppm	
US. ACGIH Threshold Limit Value	S		
Components	Туре	Value	
Carbon Dioxide (CAS 124-38-9)	STEL	30000 ppm	
	TWA	5000 ppm	
Cyclohexane (CAS 110-82-7)	TWA	100 ppm	
Isopropyl Alcohol (CAS 67-63-0)	STEL	400 ppm	
	TWA	200 ppm	
n-Hexane (CAS 110-54-3)	TWA	50 ppm	
US. NIOSH: Pocket Guide to Chen	nical Hazards		
Components	Туре	Value	
Carbon Dioxide (CAS 124-38-9)	STEL	54000 mg/m3	
duct name: 14 OZ MSI PRFSSNL TECH			SDS
AUGUNANIE. 14 OZ WOLLIN SONLILON			3 /

US. NIOSH: Pocket Guide to Chemical Hazards Components Type

Components	Туре	Value	
		30000 ppm	
	TWA	9000 mg/m3	
		5000 ppm	
Cyclohexane (CAS 110-82-7)	TWA	1050 mg/m3	
,		300 ppm	
Isopropyl Alcohol (CAS 67-63-0)	STEL	1225 mg/m3	
,		500 ppm	
	TWA	980 mg/m3	
		400 ppm	
n-Hexane (CAS 110-54-3)	TWA	180 mg/m3	
		50 ppm	
logical limit values			
ACGIH Biological Exposure Indice	es		

Components	Value	Determinant	Specimen	Sampling Time
Isopropyl Alcohol (CAS 67-63-0)	40 mg/l	Acetone	Urine	*
n-Hexane (CAS 110-54-3)	0.4 mg/l	2,5-Hexanedio n, without hydrolysis	Urine	*

* - For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation	
--	--

n-Hexane (CAS 110-54-3)

US ACGIH Threshold Limit Values: Skin designation

n-Hexane (CAS 110-54-3)

Can be absorbed through the skin.

SDS US 4 / 11

Can be absorbed through the skin.

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Eye/face protection	Chemical respirator with organic vapor cartridge and full facepiece.
Skin protection	
Hand protection	Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.
Other	Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.
Respiratory protection	Chemical respirator with organic vapor cartridge and full facepiece.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state	Liquid.
Form	Aerosol.
Color	Not available.
Odor	Not available.
Odor threshold	Not available.
рН	Not applicable estimated
Melting point/freezing point	Not available.

Initial boiling point and boiling range	Not available.
Flash point	-15.0 °F (-26.1 °C) Concentrate estimated
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or exp	losive limits
Flammability limit - lower (%)	2.5 % estimated
Flammability limit - upper (%)	12 % estimated
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	60 - 85 psig @ 70F estimated
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	526.46 °F (274.7 °C) estimated
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Density	0.72 g/cm3 estimated
Explosive properties	Not explosive.
Heat of combustion	38.77 kJ/g estimated
Heat of combustion (NFPA 30B)	38.77 kJ/g estimated
Oxidizing properties	Not oxidizing.
Percent volatile	97 % estimated
Specific gravity	0.701 estimated estimated
VOC (Weight %)	97 % estimated

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Acids. Strong oxidizing agents. Isocyanates. Chlorine.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	May cause damage to organs through prolonged or repeated exposure by inhalation. May cause drowsiness and dizziness. Headache. Nausea, vomiting.
Skin contact	Causes skin irritation.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

Product name: 14 OZ MSI PRFSSNL	ECH-SOLV CLNR LB 12PK	SDS US
Product #: 1000009594 Version #: 01	Issue date: 06-23-2016	5 / 11

Symptoms related to the
physical, chemical and
toxicological characteristicsAspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness.
Headache. Nausea, vomiting. Skin irritation. May cause redness and pain.

Information on toxicological effects

Acute toxicity	May be fatal if swallowed and enters a	May be fatal if swallowed and enters airways. Narcotic effects.		
Product	Species	Test Results		
14 OZ MSI PRFSSNL TECH	H-SOLV CLNR LB 12PK			
<u>Acute</u>				
Dermal				
LD50	Rat	3350 mg/kg		
Inhalation				
LC50	Rat	437 mg/l/4h		
Oral				
LD50	Rat			
Components	Species	Test Results		
Cyclohexane (CAS 110-82-	7)			
<u>Acute</u>				
Dermal				
LD50	Rabbit	> 2000 mg/kg		
Inhalation	- <i>i</i>			
LC50	Rat	> 32880 mg/m3, 4 Hours		
		> 5540 ppm, 4 Hours		
Oral				
LD50	Rabbit	> 5000 mg/kg		
	Rat	> 5000 mg/kg		
sopropyl Alcohol (CAS 67-6	63-0)			
<u>Acute</u>				
Dermal				
LD50	Rabbit	16.4 ml/kg, 24 Hours		
Inhalation				
LC50	Rat	> 10000 ppm, 6 Hours		
Oral				
LD50	Rat	5.84 g/kg		
	otreated Light (CAS 64742-49-0)			
<u>Acute</u>				
Dermal	Cuince nia: Debbit			
LD50	Guinea pig; Rabbit	> 9.4 ml/kg, 24 Hours		
	Rabbit	> 1900 mg/kg, 24 Hours		
Inhalation				
LC50	Rat	> 5000 mg/m3, 4 Hours		
		> 4980 mg/m3		
		> 4980 mg/m3, 4 Hours		

		13700 ppm, 4 Hours
Oral		
LD50	Rat	4820 mg/kg
n-Hexane (CAS 110-54-3)		
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg, 4 Hours

> 4.96 mg/l, 4 Hours

sds us 6 / 11

Components	Species	Test Results	
		> 5 ml/kg, 4 Hours	
Inhalation			
LC50	Rat	> 5000 ppm, 24 Hours	
		> 31.86 mg/l	
		73860 ppm, 4 Hours	
Oral			
LD50	Rat	24 ml/kg	
		24 g/kg	
	Wistar rat	49 g/kg	
* Estimates for product may b	be based on additional component data not sh	iown.	
Skin corrosion/irritation	Causes skin irritation.		
Serious eye damage/eye rritation	Direct contact with eyes may cause tempor	rary irritation.	
Respiratory or skin sensitizatio	n		
Respiratory sensitization	Not a respiratory sensitizer.		
Skin sensitization	This product is not expected to cause skin sensitization.		
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.		
Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.		
IARC Monographs. Overall Not listed.	Evaluation of Carcinogenicity		
OSHA Specifically Regulate	ed Substances (29 CFR 1910.1001-1050)		
Not regulated.			
•••	ogram (NTP) Report on Carcinogens		
Not listed. Reproductive toxicity	Suspected of damaging fertility.		
Specific target organ toxicity -	May cause drowsiness and dizziness.		
single exposure			
Specific target organ toxicity - repeated exposure	May cause damage to organs through prolonged or repeated exposure.		
Aspiration hazard	May be fatal if swallowed and enters airways.		
Chronic effects	May cause damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful.		
12. Ecological information	ı		
Ecotoxicity	Toxic to aquatic life with long lasting effects	S	

toxicity	Toxic to a	equatic life with long lasting effects.		
Product		Species	Test Results	
14 OZ MSI PRFSSNL	TECH-SOLV CLN	R LB 12PK		
Aquatic				
Algae	IC50	Algae	3537 mg/L, 72 Hours	
Crustacea	EC50	Daphnia	627 mg/L, 48 Hours	
Fish	LC50	Fish	9.1039 mg/L, 96 Hours	
Components		Species	Test Results	
Cyclohexane (CAS 11	0-82-7)			
Aquatic				
Fish	LC50	Fathead minnow (Pimephales promelas)	23.03 - 42.07 mg/l, 96 hours	
Isopropyl Alcohol (CA	S 67-63-0)			
Aquatic				
Algae	IC50	Algae	1000.0001 mg/L, 72 Hours	
Crustacea	EC50	Daphnia	13299 mg/L, 48 Hours	
duct name: 14 OZ MSI P	RFSSNL TECH-SOL	V CLNR LB 12PK		SDS I
duct #: 1000009594 Ve	rsion #: 01 Issue da	te [.] 06-23-2016		7 / 1

Components		Species	Test Results
Fish	LC50	Bluegill (Lepomis macrochirus)	> 1400 mg/l, 96 hours
n-Hexane (CAS 110-5	4-3)		
Aquatic			
Fish	LC50	Fathead minnow (Pimephales prome	elas) 2.101 - 2.981 mg/l, 96 hours
rsistence and degrada	bility No data is	additional component data not shown. s available on the degradability of this prod	luct.
Partition coefficient	n-octanol / water (log Kow)	
Cyclohexane		3.44	
Isopropyl Alcohol		0.05	
n-Hexane		3.9	

Mobility in soil	No data available.
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

14. Transport information

DOT

UN number	UN1950
UN proper shipping name	Aerosols, flammable, (each not exceeding 1 L capacity)
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
Special provisions	N82
Packaging exceptions	306
Packaging non bulk	None
Packaging bulk	None
T I: I I I I I I I	

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

sds Us 8 / 11

IATA

UN number	UN1950
UN proper shipping name	Aerosols, flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.

Environmental hazards	Yes
ERG Code	10L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed with restrictions.
Cargo aircraft only	Allowed with restrictions.
Packaging Exceptions	LTD QTY
IMDG	
UN number	UN1950
UN proper shipping name Transport hazard class(es)	AEROSOLS
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Environmental hazards	
Marine pollutant	Yes
EmS	F-D, S-U
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
Packaging Exceptions	LTD QTY
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.







General information

DOT Regulated Marine Pollutant. IMDG Regulated Marine Pollutant.

Product name: 14 OZ MSI PRFSSNL TECH-SOLV CLNR LB 12PK Product #: 1000009594 Version #: 01 Issue date: 06-23-2016

sds us 9 / 11

15. Regulatory information

LIS fodoral regulations	This product is a "Hozarday	is Chamical" as defin	ad by the OSHA Hazard Communication	
US federal regulations	Standard, 29 CFR 1910.12		ed by the OSHA Hazard Communication	
TSCA Section 12(b) Export	TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)			
Not regulated.				
CERCLA Hazardous Subst	ance List (40 CFR 302.4)			
Cyclohexane (CAS 110-	,	Listed.		
n-Hexane (CAS 110-54-	,	Listed.		
SARA 304 Emergency relea	ase notification			
Not regulated.	ed Substances (29 CFR 1910	1001-1050)		
Not regulated.				
0	agutharization Act of 1096 (
Superfund Amendments and R Hazard categories	Immediate Hazard - Yes	DARA)		
Hazard categories	Delayed Hazard - Yes			
	Fire Hazard - Yes			
	Pressure Hazard - No			
SABA 202 Extremely bazar	Reactivity Hazard - No			
SARA 302 Extremely hazar Not listed.				
SARA 311/312 Hazardous chemical	No			
SARA 313 (TRI reporting)				
Chemical name		CAS number	% by wt.	
n-Hexane		110-54-3	20 - 40	
Cyclohexane		110-82-7	1 - 2.5	
Other federal regulations				
Clean Air Act (CAA) Sectio	n 112 Hazardous Air Polluta	nts (HAPs) List		
n-Hexane (CAS 110-54-				
	n 112(r) Accidental Release	Prevention (40 CFR	68.130)	
Not regulated.				
Safe Drinking Water Act (SDWA)	Not regulated.			
US state regulations				
US. California Controlled S	ubstances. CA Department	of Justice (California	a Health and Safety Code Section 11100)	
Not listed.				
US. California. Candidate C (a))	Chemicals List. Safer Consur	mer Products Regul	ations (Cal. Code Regs, tit. 22, 69502.3, subd.	
Isopropyl Alcohol (CAS	67-63-0)			
Naphtha, (Petroleum), Hydrotreated Light (CAS 64742-49-0)				
n-Hexane (CAS 110-54-3) US. Massachusetts RTK - Substance List				
Carbon Dioxide (CAS 124-38-9) Cyclohexane (CAS 110-82-7)				
Isopropyl Alcohol (CAS 67-63-0)				
n-Hexane (CAS 110-54-3)				

US. New Jersey Worker and Community Right-to-Know Act

Carbon Dioxide (CAS 124-38-9) Cyclohexane (CAS 110-82-7) Isopropyl Alcohol (CAS 67-63-0) n-Hexane (CAS 110-54-3)

US. Pennsylvania Worker and Community Right-to-Know Law

Carbon Dioxide (CAS 124-38-9) Cyclohexane (CAS 110-82-7) Isopropyl Alcohol (CAS 67-63-0) n-Hexane (CAS 110-54-3)

US. Rhode Island RTK

Cyclohexane (CAS 110-82-7)

Product name: 14 OZ MSI PRFSSNL TECH-SOLV CLNR LB 12PK Product #: 1000009594 Version #: 01 Issue date: 06-23-2016 sds us 10 / 11 Isopropyl Alcohol (CAS 67-63-0) n-Hexane (CAS 110-54-3)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Benzene (CAS 71-43-2) Listed: February 27, 1987

US - California Proposition 65 - CRT: Listed date/Developmental toxin

Benzene (CAS 71-43-2)Listed: December 26, 1997Toluene (CAS 108-88-3)Listed: January 1, 1991US - California Proposition 65 - CRT: Listed date/Male reproductive toxin

Benzene (CAS 71-43-2) Listed: December 26, 1997

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	06-23-2016
Version #	01
Disclaimer	Sprayway, Inc. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.
Revision information	This document has undergone significant changes and should be reviewed in its entirety.

Product name: 14 OZ MSI PRFSSNL TECH-SOLV CLNR LB 12PK	SDS US
Product #: 1000009594 Version #: 01 Issue date: 06-23-2016	11 / 11